

# **EUROLITE LED KKL-50 Floodlight 4100K silver**

50 W LED floodlight with extension arm and screw terminal for fixation


Art. No.: 41600470 GTIN: 4026397603248











incl. 19% VAT.

### **Description:**

The Eurolite KKL-50 LED floodlight illuminates trade fair booths, shop windows, workshops and even weatherproof outdoor areas.

You can purchase the KKL-50 in three simple casing colors: black, white and silver.

## Features:

- Unique design
- For tabletops with up to 40 mm strength
- 1 powerful LED 50 W COB (chip-on-board) neutral white (NW)
- The device is cooled by passive convection cooling
- Control via plug and play
- Easy installation
- With a beam angle of 75°
- Very high color rendering index (CRI)
- Various versions available
- Silent operation
- For application areas such as: Advertisement/Shop window; Trade fair and shop fitting
- Application possibility: Suspended; wall mounting

## Package contents

- 1 x spotlight, 1 x knurled screw, 1 x plate, 1 x user manual

# **Technical specifications:**

Power supply: 100-240 V AC, 50/60 Hz

### Logistic

EAN / GTIN: 4026397603248

Weight: 2,36 kg Length: 0.65 m Width: 0.21 m Heigth: 0.11 m

Power consumption:	50 W
IP classification:	IP20
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 1,0 mm² H05RN-F
Cable length:	Approx. 0,8 m
Lamp type:	LED lamp
LED type:	1 x 50 W COB (chip-on-board) neutral white (NW)
Cooling:	Passive convection cooling
Control:	Plug and play
Setup:	Easy installation
Beam angle:	75°
Beam angle (1/2 peak):	75°
Beam angle (1/10 peak):	125°
Color temperature:	4100K
Color rendering index (CRI):	90 Ra
Luminous flux:	3769 lm
Housing color:	Silver
Dimensions:	Length: 64 cm
	Width: 20,5 cm
	Depth: 8,5 cm
Weight:	2 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	G
EPREL-Nr:	1273332