

EUROLITE LED Theatre COB 100 WW

LED theatre spot with warm white (WW) 100 W COB (chip-on-board) LED

Art. No.: 41602010

GTIN: 4026397676266



List price: 236.81 €

incl. 19% VAT.

Features:

- 1 powerful LED 100 W COB (chip-on-board) warm white (WW)
 - Dimmer electronic
 - Strobe effect
 - Integrated show programs
 - The device is cooled by cooling fan
 - Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
 - Flicker-free
 - With a beam angle of 40°
 - Very high color rendering index (CRI)
 - With double bracket
 - 4 digit 7-segment LED display
 - Very quiet working noise
 - For application areas such as: Theater; clubs/dancing school; stage; mobile djs / entertainer
 - Mains input and output for power linking up to 8 units
 - Application possibility: Standing; suspended; on stand
 - Preprogrammed in Light´J; Light Captain; Colorchief
- Package contents**
- 1 x spotlight, 1 x power cord, 1 x user manual

Logistic

EAN / GTIN: 4026397676266

Weight: 3,10 kg

Length: 0.26 m

Width: 0.23 m

Height: 0.34 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	85 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug included
Power output:	P-Con (gray), mounting version
Fuse:	T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 100 W COB (chip-on-board) warm white (WW)
Flash rate:	0 - 20 Hz
DMX channels:	1; 4
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light´J; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	40°
Beam angle (1/2 peak):	40°
Beam angle (1/10 peak):	70°
Color temperature:	3100K
Color rendering index (CRI):	96 Ra
Illuminance in Lux (lx):	Warm white (WW) 1m: 5692 lx, 3m: 680 lx, 6m: 180 lx
Housing color:	Black matte
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Material:	Plastic; metal
Dimensions:	Width: 24,3 cm Depth: 31,1 cm Height: 32 cm
Weight:	2,75 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 1,0 mm² H05VV-F
Cable length:	Approx. 1,2 m
Mounting bracket	
Diameter mounting holes:	1 x Ø11mm
Material:	Metal, 2,5 mm
Barndoor	

Material:	Metal, 0,8 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting