

## EUROLITE LED Theatre COB 100 WW

LED theatre spot with warm white (WW) 100 W COB (chip-on-board) LED

Art. No.: 41602010

GTIN: 4026397676266



**List price: 236.81 €**

incl. 19% VAT.

### Features:

- 1 powerful LED 100 W COB (chip-on-board) warm white (WW)
  - Dimmer electronic
  - Strobe effect
  - Integrated show programs
  - The device is cooled by cooling fan
  - Control via stand-alone; DMX; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
  - Flicker-free
  - With a beam angle of 40°
  - Very high color rendering index (CRI)
  - With double bracket
  - 4 digit 7-segment LED display
  - Very quiet working noise
  - For application areas such as: Theater; Clubs/dancing school; Stage; mobile djs / entertainer
  - Preprogrammed in Light´J; Light Captain
  - Mains input and output for power linking up to 8 units
  - Application possibility: Standing; suspended; on stand
- Package contents**
- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x barn door

### Logistic

EAN / GTIN: 4026397676266

Weight: 3,10 kg

Length: 0.26 m

Width: 0.23 m

Height: 0.34 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	85 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	T 1 A Fuse replaceable
Lamp type:	LED lamp
LED:	1 x 100 W COB (chip-on-board) warm white (WW)
Color temperature:	3100K
Flash rate:	0 - 20 Hz
DMX channels:	1; 4
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light J; Light Captain
Projection:	Flicker-free
Beam angle:	40°
Beam angle (1/2 peak):	40°
Beam angle (1/10 peak):	70°
Color rendering index (CRI):	95 Ra
Illuminance in Lux (lx):	Warm white (WW) 1m: 4025 lx, 3m: 521 lx, 6m: 155 lx
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 24,3 cm Depth: 31,1 cm Height: 32 cm
Weight:	2,75 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)
Photobiological safety:	Risk Group 0
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting