

EUROLITE LED Theatre COB 200 WW/CW

LED theatre spot with 2in1 BCL CW/WW W COB (chip-on-board) LED

Art. No.: 41602034

GTIN: 4026397686548



List price: 427.21 €

incl. 19% VAT.

Features:

- 1 powerful LED COB (chip-on-board) 2in1 BCL CW/WW (homogenous color mix)
 - Variable color temperature 2500 K - 5700 K
 - Dimmer electronic
 - Strobe effect
 - Integrated show programs
 - The device is cooled by cooling fan
 - Control via stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
 - Flicker-free
 - With a beam angle of 17°
 - Very high color rendering index (CRI)
 - With double bracket
 - LCD display
 - Very quiet working noise
 - For application areas such as: Theater; Trade fair and shop fitting; installation; stage
 - Mains input and output for power linking up to 8 units
 - Application possibility: Standing; suspended; on stand
 - Preprogrammed in Light´J; Light Captain; Colorchief
- Package contents**
- 1 x device, 1 x power cord, 1 x remote control, 1 x user manual

Logistic

EAN / GTIN: 4026397686548

Weight: 4,96 kg

Length: 0.45 m

Width: 0.31 m

Height: 0.28 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	150 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	1 x COB (chip-on-board) 2in1 BCL CW/WW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 4; 5; 7
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W- DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light´J; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	17°
Beam angle (1/2 peak):	17°
Beam angle (1/10 peak):	35°
Color temperature:	2500K - 5700K adjustable
Color rendering index (CRI):	98 Ra
Housing color:	Black matte
Attachment system:	Double bracket
Display type:	LCD display
Material:	Aluminum casting
Dimensions:	Width: 25,95 cm Depth: 20,00 cm Height: 37,65 cm
Weight:	4,11 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)
Photobiological safety:	Risk Group 0
Mounting bracket	
Diameter mounting holes:	3 x Ø11mm
Material:	Metal, 2,5 mm
Power cord	
Cable construction:	3 x 1,0 mm² H05VV-F
Cable length:	Approx. 1,2 m

Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting