

EUROLITE LED Theatre COB 200 RGB+WW

LED theatre spot with 200 W COB LED, RGB+WW

Art. No.: 41602038

GTIN: 4026397686531



List price: 415.31 €

incl. 19% VAT.

Features:

- Ideal for colorful light in theaters, on concert stages, clubs and many other venues
- Dimmer and strobe effect
- Direct color selection for 27 preset colors
- Supports QuickDMX - the wireless DMX system from Eurolite
- Mains input and output for power linking up to 8 units
- 1 powerful LED COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix)
- Integrated Showprograms
- Can be operated in 3; 4; 5; 6; 10 CH mode
- The device is cooled by cooling fan
- Controlling by stand-alone; IR remote control; DMX; Master/slave function; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); Sound to light
- Preprogrammed in Light'J; Light Captain
- Flicker-free projection
- With a beam angle of 17°
- Very high color rendering index (CRI)
- With Mounting bracket
- With double bracket
- LCD display for easy controlling

Logistic

EAN / GTIN: 4026397686531

Weight: 4,96 kg

Length: 0.45 m

Width: 0.31 m

Height: 0.28 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 140 W

IP classification:	IP20
Protection class:	Class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Lamp type:	LED lamp
LED:	1 x COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix)
Color temperature:	1800K - 8000K adjustable
Flash rate:	0 - 20 Hz
DMX channels:	3; 4; 5; 6; 10
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; IR remote control; DMX; Master/slave function; Sound to light via Microphone; Light 'J; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); Light Captain; Sound to light
Beam angle:	17°
Beam angle (1/2 peak):	17°
Beam angle (1/10 peak):	35°
Color rendering index (CRI) more than:	95 Ra
Housing color:	Black
Attachment system:	Mounting bracket Double bracket
Display type:	LCD display
Dimensions:	Width: 25,95 cm Depth: 20,00 cm Height: 37,65 cm
Weight:	4,11 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese (provided)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting