

# **EUROLITE LED THA-20PC TRC Theater-Spot wh**

Fanless PC spot with 17 W white light LED, color rendering index (CRI) >90

Art. No.: 41602072 GTIN: 4026397693126





**List price: 201.11 €** 

incl. 19% VAT.

## Features:

- New LED technology that simulates the color temperature curve of a halogen lamp when dimming
- Two additional frost filters provide a soft, homogeneous light
- 1 powerful LED 17 W COB (chip-on-board) Dim to warm
- The device is cooled by passive convection cooling
- Control via stand-alone; quick select potentiometer for brightness
- Flicker-free
- With a beam angle of 17°
- Very high color rendering index (CRI)
- With mounting bracket
- For application areas such as: Trade fair and shop fitting; wedding/gala/events; installation; restaurants, bars and hotels
- Dimmer electronic
- Rubber feet
- Silent operation
- Application possibility: Suspended; on stand

## Package contents

- 1 x spotlight, 1 x user manual, 1 x barndoor, 2 x frost filter

### **Technical specifications:**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	22 W
IP classification:	IP20

### Logistic

EAN / GTIN: 4026397693126

Weight: 2,75 kg Length: 0.32 m Width: 0.20 m Heigth: 0.26 m

Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Fuse:	5 x 20 mm, T 1 A fuse replaceable
LED type:	1 x 17 W COB (chip-on-board) Dim to warm
Cooling:	Passive convection cooling
Control:	Stand-alone; quick select potentiometer for brightness
Projection:	Flicker-free
Beam angle:	17°
Beam angle (1/2 peak):	17° Frost filter 19° Frost filter 26°
Beam angle (1/10 peak):	36° Frost filter 40° Frost filter 53°
Color temperature:	3000K
Color temperature:  Color rendering index (CRI):	3000K 92 Ra
Color rendering index (CRI):	92 Ra
Color rendering index (CRI):  Illuminance in Lux (lx):	92 Ra Warm white (WW) 3m: 727 lx, 6m: 188 lx
Color rendering index (CRI):  Illuminance in Lux (lx):  Housing color:	92 Ra  Warm white (WW) 3m: 727 lx, 6m: 188 lx  White
Color rendering index (CRI):  Illuminance in Lux (lx):  Housing color:  Attachment system:	92 Ra  Warm white (WW) 3m: 727 lx, 6m: 188 lx  White  Mounting bracket
Color rendering index (CRI):  Illuminance in Lux (lx):  Housing color:  Attachment system:  Transport aid:	92 Ra  Warm white (WW) 3m: 727 lx, 6m: 188 lx  White  Mounting bracket  Rubber feet  Length: 21,5 cm  Width: 14,5 cm
Color rendering index (CRI):  Illuminance in Lux (lx):  Housing color:  Attachment system:  Transport aid:  Dimensions:	92 Ra  Warm white (WW) 3m: 727 lx, 6m: 188 lx  White  Mounting bracket  Rubber feet  Length: 21,5 cm  Width: 14,5 cm  Depth: 21 cm
Color rendering index (CRI):  Illuminance in Lux (lx):  Housing color:  Attachment system:  Transport aid:  Dimensions:	92 Ra  Warm white (WW) 3m: 727 lx, 6m: 188 lx  White  Mounting bracket  Rubber feet  Length: 21,5 cm  Width: 14,5 cm  Depth: 21 cm  2,23 kg
Color rendering index (CRI):  Illuminance in Lux (lx):  Housing color:  Attachment system:  Transport aid:  Dimensions:  Weight:  Noise classification:	92 Ra  Warm white (WW) 3m: 727 lx, 6m: 188 lx  White  Mounting bracket  Rubber feet  Length: 21,5 cm  Width: 14,5 cm  Depth: 21 cm  2,23 kg