eurolite®

EUROLITE LED THA-40PC Theater Spot wh

Fanless PC spot (DMX), warm white 57 W LED, color rendering index (CRI) >90

Art. No.: 41602081 GTIN: 4026397578867











List price: 374.85 €

incl. 19% VAT.

Features:

- 1 powerful LED 57 W COB (chip-on-board) warm white (WW)
- Strobe effect
- The device is cooled by passive convection cooling
- Control via RDM; stand-alone; DMX
- Flicker-free
- With a beam angle of 11° 48°
- Very high color rendering index (CRI)
- With mounting bracket
- LCD display
- Dimmer electronic; dimmer curves with adjustable response; Dimmer speed (step response) adjustable
- Preprogrammed in LED PC-Control 512; Light Captain; Light'J; Colorchief
- Rubber feet
- For application areas such as: Wedding/gala/events; Trade fair and shop fitting; stage; theater
- Silent operation
- Application possibility: Suspended; on stand Package contents
- 1 x spotlight, 1 x user manual, 1 x barndoor

Technical specifications:

| Power supply: | 100-240 V AC, 50/60 Hz |
|--------------------|------------------------|
| Power consumption: | 40 W |
| IP classification: | IP20 |

Logistic

EAN / GTIN: 4026397578867 Weight: 4,29 kg Length: 0.34 m Width: 0.27 m Heigth: 0.22 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| Power connection: | Fixed power supply cord with safety plug |
|------------------------------|---|
| LED type: | 1 x 57 W COB (chip-on-board) warm white (WW) |
| DMX channels: | 1; 2 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | RDM; stand-alone; DMX |
| Preprogrammed in: | LED PC-Control 512; Light Captain; Light´J; Colorchief |
| Projection: | Flicker-free |
| Beam angle: | 11° - 48° |
| Beam angle (1/2 peak): | 11 - 37° |
| Beam angle (1/10 peak): | 17 - 48° |
| Color temperature: | 3100K |
| Color rendering index (CRI): | 91 Ra |
| Illuminance in Lux (lx): | Warm white (WW) 3m: 1656 lx, 6m: 424 lx |
| Housing color: | White |
| Attachment system: | Mounting bracket |
| Display type: | LCD display |
| Transport aid: | Rubber feet |
| Dimensions: | Length: 27,5 cm Width: 20,5 cm Depth: 25 cm |
| Weight: | 3,84 kg |
| Noise classification: | Class 0 (no noise at all) |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |
| | |