

EUROLITE LED THA-40PC TRC Theater Spot bk

Fanless PC spot with 57 W white light LED, color rendering index (CRI) >90

Art. No.: 41602082 GTIN: 4026397621631









List price: 272.51 €

incl. 19% VAT.

Features:

- Rugged metal housing
- 1 powerful LED 57 W COB (chip-on-board) warm white (WW)
- Dimmer electronic
- The device is cooled by passive convection cooling
- Control via stand-alone; rotary dial for brightness; Dimmer
- Flicker-free
- With a beam angle of 12° 47°
- Very high color rendering index (CRI)
- With mounting bracket
- Silent operation
- For application areas such as: Trade fair and shop fitting; wedding/gala/events; restaurants, bars and hotels; video and photography
- Rubber feet

Package contents

- 1 x spotlight, 1 x barndoor, 1 x filter frame, 1 x user manual

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	40 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug

Logistic

EAN / GTIN: 4026397621631

Weight: 4,30 kg Length: 0.34 m Width: 0.27 m Heigth: 0.22 m

Fuse:	5 x 20 mm, T 1 A fuse replaceable
LED type:	1 x 57 W COB (chip-on-board) warm white (WW)
Cooling:	Passive convection cooling
Control:	Stand-alone; rotary dial for brightness; Dimmer
Projection:	Flicker-free
Beam angle:	12° - 47°
Beam angle (1/2 peak):	12 - 36°
Beam angle (1/10 peak):	18 - 47°
Color temperature:	3100K
Color rendering index (CRI):	92 Ra
Illuminance in Lux (lx):	Narrow 3m: 2008 lx, 6m: 514 lx Wide 3m: 482 lx, 6m: 141 lx
Housing color:	Black
Attachment system:	Mounting bracket
Transport aid:	Rubber feet
Material:	Aluminum casting
Slot for spot length:	13,1 cm x 13,1 cm
Dimensions:	Length: 26 cm
	Width: 20 cm
····	Depth: 25 cm
Weight:	3,82 kg
Naine alegations	
Noise classification:	Class 0 (no noise at all)
Mounting bracket	
Mounting bracket Diameter mounting holes:	1 x Ø10mm; 2 x Ø6mm
Mounting bracket Diameter mounting holes: Material:	
Mounting bracket Diameter mounting holes: Material: Power cord	1 x Ø10mm; 2 x Ø6mm Metal, 3 mm
Mounting bracket Diameter mounting holes: Material: Power cord Cable construction:	1 x Ø10mm; 2 x Ø6mm Metal, 3 mm 3 x 0,75 mm² H05VV-F
Mounting bracket Diameter mounting holes: Material: Power cord Cable construction: Cable length:	1 x Ø10mm; 2 x Ø6mm Metal, 3 mm
Mounting bracket Diameter mounting holes: Material: Power cord Cable construction: Cable length: Barndoor	1 x Ø10mm; 2 x Ø6mm Metal, 3 mm 3 x 0,75 mm² H05VV-F Approx. 1 m
Mounting bracket Diameter mounting holes: Material: Power cord Cable construction: Cable length: Barndoor Material:	1 x Ø10mm; 2 x Ø6mm Metal, 3 mm 3 x 0,75 mm² H05VV-F Approx. 1 m Aluminum, 1,5 mm; metal
Mounting bracket Diameter mounting holes: Material: Power cord Cable construction: Cable length: Barndoor	1 x Ø10mm; 2 x Ø6mm Metal, 3 mm 3 x 0,75 mm² H05VV-F Approx. 1 m Aluminum, 1,5 mm; metal Outside: 12,9 mm
Mounting bracket Diameter mounting holes: Material: Power cord Cable construction: Cable length: Barndoor Material: Ring diameter:	1 x Ø10mm; 2 x Ø6mm Metal, 3 mm 3 x 0,75 mm² H05VV-F Approx. 1 m Aluminum, 1,5 mm; metal
Mounting bracket Diameter mounting holes: Material: Power cord Cable construction: Cable length: Barndoor Material:	1 x Ø10mm; 2 x Ø6mm Metal, 3 mm 3 x 0,75 mm² H05VV-F Approx. 1 m Aluminum, 1,5 mm; metal Outside: 12,9 mm
Mounting bracket Diameter mounting holes: Material: Power cord Cable construction: Cable length: Barndoor Material: Ring diameter:	1 x Ø10mm; 2 x Ø6mm Metal, 3 mm 3 x 0,75 mm² H05VV-F Approx. 1 m Aluminum, 1,5 mm; metal Outside: 12,9 mm Inside: 10,9 mm
Mounting bracket Diameter mounting holes: Material: Power cord Cable construction: Cable length: Barndoor Material: Ring diameter: Filter frame Diameter mounting holes:	1 x Ø10mm; 2 x Ø6mm Metal, 3 mm 3 x 0,75 mm² H05VV-F Approx. 1 m Aluminum, 1,5 mm; metal Outside: 12,9 mm Inside: 10,9 mm
Mounting bracket Diameter mounting holes: Material: Power cord Cable construction: Cable length: Barndoor Material: Ring diameter: Filter frame Diameter mounting holes: Shape:	1 x Ø10mm; 2 x Ø6mm Metal, 3 mm 3 x 0,75 mm² H05VV-F Approx. 1 m Aluminum, 1,5 mm; metal Outside: 12,9 mm Inside: 10,9 mm 1 x Ø4mm Octagonal
Mounting bracket Diameter mounting holes: Material: Power cord Cable construction: Cable length: Barndoor Material: Ring diameter: Filter frame Diameter mounting holes: Shape: Material:	1 x Ø10mm; 2 x Ø6mm Metal, 3 mm 3 x 0,75 mm² H05VV-F Approx. 1 m Aluminum, 1,5 mm; metal Outside: 12,9 mm Inside: 10,9 mm 1 x Ø4mm Octagonal Aluminum, 0,8 mm
Mounting bracket Diameter mounting holes: Material: Power cord Cable construction: Cable length: Barndoor Material: Ring diameter: Filter frame Diameter mounting holes: Shape: Material:	1 x Ø10mm; 2 x Ø6mm Metal, 3 mm 3 x 0,75 mm² H05VV-F Approx. 1 m Aluminum, 1,5 mm; metal Outside: 12,9 mm Inside: 10,9 mm 1 x Ø4mm Octagonal Aluminum, 0,8 mm Width: 13 cm
Mounting bracket Diameter mounting holes: Material: Power cord Cable construction: Cable length: Barndoor Material: Ring diameter: Filter frame Diameter mounting holes: Shape: Material:	1 x Ø10mm; 2 x Ø6mm Metal, 3 mm 3 x 0,75 mm² H05VV-F Approx. 1 m Aluminum, 1,5 mm; metal Outside: 12,9 mm Inside: 10,9 mm 1 x Ø4mm Octagonal Aluminum, 0,8 mm Width: 13 cm Height: 13 cm
Mounting bracket Diameter mounting holes: Material: Power cord Cable construction: Cable length: Barndoor Material: Ring diameter: Filter frame Diameter mounting holes: Shape: Material: Dimensions:	1 x Ø10mm; 2 x Ø6mm Metal, 3 mm 3 x 0,75 mm² H05VV-F Approx. 1 m Aluminum, 1,5 mm; metal Outside: 12,9 mm Inside: 10,9 mm 1 x Ø4mm Octagonal Aluminum, 0,8 mm Width: 13 cm Height: 13 cm