

EUROLITE LED THA-40PC TRC Theater Spot bk

Fanless PC spot with 57 W white light LED, color rendering index (CRI) >90

Art. No.: 41602082

GTIN: 4026397621631



Features:

- Rugged metal housing
- 1 LED 57 W COB (chip-on-board) warm white (WW)
- Dimmer electronic
- The device is cooled by passive convection cooling
- Control via stand-alone; rotary dial for brightness; Dimmer
- Flicker-free
- With a beam angle of 12° - 47°
- Very high color rendering index (CRI)
- With mounting bracket
- Rubber feet
- Silent operation
- For application areas such as: Decoration; Trade fair and shop fitting; restaurants, bars and hotels; video and photography; advertisement/Shop window

Logistic

EAN / GTIN: 4026397621631  
Weight: 4,30 kg  
Length: 0.34 m  
Width: 0.27 m  
Heigh: 0.22 m

Technical specifications:

|                    |                                          |
|--------------------|------------------------------------------|
| Power supply:      | 100-240 V AC, 50/60 Hz                   |
| Power consumption: | 40 W                                     |
| IP classification: | IP20                                     |
| Protection class:  | Protection class I                       |
| Power connection:  | Fixed power supply cord with safety plug |
| Fuse:              | 5 x 20 mm, T 1 A fuse replaceable        |

|                              |                                                               |
|------------------------------|---------------------------------------------------------------|
| Lamp type:                   | LED lamp                                                      |
| LED type:                    | 1 x 57 W COB (chip-on-board) warm white (WW)                  |
| Cooling:                     | Passive convection cooling                                    |
| Control:                     | Stand-alone; rotary dial for brightness; Dimmer               |
| Projection:                  | Flicker-free                                                  |
| Beam angle:                  | 12° - 47°                                                     |
| Beam angle (1/2 peak):       | 12 - 36°                                                      |
| Beam angle (1/10 peak):      | 18 - 47°                                                      |
| Color temperature:           | 3100K                                                         |
| Color rendering index (CRI): | 92 Ra                                                         |
| Illuminance in Lux (lx):     | Narrow 3m: 2008 lx, 6m: 514 lx<br>Wide 3m: 482 lx, 6m: 141 lx |
| Housing color:               | Black                                                         |
| Attachment system:           | Mounting bracket                                              |
| Transport aid:               | Rubber feet                                                   |
| Material:                    | Aluminum casting                                              |
| Slot for spot length:        | 13.1 cm x 13.1 cm                                             |
| Dimensions:                  | Length: 26 cm<br>Width: 20 cm<br>Depth: 25 cm                 |
| Weight:                      | 3.82 kg                                                       |
| Noise classification:        | Class 0 (no noise at all)                                     |
| Diameter mounting holes:     | 1 x Ø10mm; 2 x Ø6mm                                           |
| Material:                    | Metal, 3 mm                                                   |
| Cable construction:          | 3 x 0.75 mm² H05VV-F                                          |
| Cable length:                | Approx. 1 m                                                   |
| Material:                    | Aluminum, 1.5 mm; metal                                       |
| Ring diameter:               | Outside: 12.9 mm<br>Inside: 10.9 mm                           |
| Diameter mounting holes:     | 1 x Ø4mm                                                      |
| Shape:                       | Octagonal                                                     |
| Material:                    | Aluminum, 0.8 mm                                              |
| Dimensions:                  | Width: 13 cm<br>Height: 13 cm<br>Diameter: Ø 10.5 cm          |
| Special product:             | Not designed for household room illumination                  |
| Intended use:                | Show effect lighting                                          |

## Scope of delivery:

1 x spotlight  
 1 x barndoor  
 1 x filter frame  
 1 x user manual