

EUROLITE LED THA-60PC Theater Spot

Spot with 60 W COB LED (RGBW) and plano-convex lens, extremely quiet, DMX

Art. No.: 41602110 GTIN: 4026397566604









List price: 427.21 €

incl. 19% VAT.

Features:

- With plano-convex lens
- Compact design
- 1 powerful LED 60 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX
- Flicker-free
- With a beam angle of 7° 48°
- With mounting bracket
- LCD display
- Dimmer electronic; color change adjustable; color fade adjustable; dimmer curves with adjustable response; Dimmer speed (step response) adjustable
- Strobe effect
- Preprogrammed in Light'J; LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Colorchief
- Very quiet working noise
- For application areas such as: Clubs/dancing school; Trade fair and shop fitting; stage; theater
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x barndoor, 1 x user manual, 1 x filter frame

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W

Logistic

EAN / GTIN: 4026397566604

Weight: 4,19 kg Length: 0.36 m Width: 0.21 m Heigth: 0.27 m

Power connection: Eixed power supply cord with safety 1 x 60 W COB (chip-on-board) 4in1 (homogenous color mix) DMX channels: 5; 6; 7 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Temperature-controlled fan Control: Stand-alone; DMX Preprogrammed in: Light'J; LED PC-Control 512; LED E OPERATOR 4x4; LED EASY OPER ATOR DELUXE; L Colorchief Projection: Flicker-free Beam angle: 7° - 48° Beam angle (1/2 peak): 7 - 39° Beam angle (1/10 peak): 14 - 48° Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm	
(homogenous color mix) DMX channels: 5; 6; 7 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Temperature-controlled fan Control: Stand-alone; DMX Preprogrammed in: Light'J; LED PC-Control 512; LED E OPERATOR 4x4; LED EASY OPER LED EASY OPER LED EASY OPERATOR DELUXE; L Colorchief Projection: Flicker-free Beam angle: 7° - 48° Beam angle (1/2 peak): 7 - 39° Beam angle (1/10 peak): 14 - 48° Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm	plug
DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Temperature-controlled fan Control: Stand-alone; DMX Preprogrammed in: Light'J; LED PC-Control 512; LED E OPERATOR 4x4; LED EASY OPER LED EASY OPER LED EASY OPERATOR DELUXE; L Colorchief Projection: Flicker-free Beam angle: 7° - 48° Beam angle (1/2 peak): 7 - 39° Beam angle (1/10 peak): 14 - 48° Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm	QCL RGBW
DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Temperature-controlled fan Control: Stand-alone; DMX Preprogrammed in: Light'J; LED PC-Control 512; LED E OPERATOR 4x4; LED EASY OPER LED EASY OPERATOR DELUXE; L Colorchief Projection: Flicker-free Beam angle: 7° - 48° Beam angle (1/2 peak): 7 - 39° Beam angle (1/10 peak): Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm	
Cooling: Temperature-controlled fan Control: Stand-alone; DMX Preprogrammed in: Light'J; LED PC-Control 512; LED E OPERATOR 4x4; LED EASY OPER LED EASY OPERATOR DELUXE; L Colorchief Projection: Flicker-free Beam angle: 7° - 48° Beam angle (1/2 peak): 7 - 39° Beam angle (1/10 peak): 14 - 48° Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm	
Control: Stand-alone; DMX Preprogrammed in: Light'J; LED PC-Control 512; LED E OPERATOR 4x4; LED EASY OPER LED EASY OPERATOR DELUXE; L Colorchief Projection: Flicker-free Beam angle: 7° - 48° Beam angle (1/2 peak): 7 - 39° Beam angle (1/10 peak): 14 - 48° Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm	
Preprogrammed in: Light'J; LED PC-Control 512; LED E OPERATOR 4x4; LED EASY OPER LED EASY OPERATOR DELUXE; L Colorchief Projection: Flicker-free Beam angle: 7° - 48° Beam angle (1/2 peak): 7 - 39° Beam angle (1/10 peak): 14 - 48° Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm	
OPERATOR 4x4; LED EASY OPER LED EASY OPERATOR DELUXE; L Colorchief Projection: Flicker-free Beam angle: 7° - 48° Beam angle (1/2 peak): 7 - 39° Beam angle (1/10 peak): 14 - 48° Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm	
Beam angle: 7° - 48° Beam angle (1/2 peak): 7 - 39° Beam angle (1/10 peak): 14 - 48° Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm	ATOR 4x6;
Beam angle (1/2 peak): Beam angle (1/10 peak): Housing color: Black Attachment system: Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm	
Beam angle (1/10 peak): Housing color: Black Attachment system: Mounting bracket LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm	
Housing color: Attachment system: Mounting bracket LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm	
Attachment system: Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm	
Display type: LCD display Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm	
Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm	
Width: 19,6 cm Depth: 17,3 cm	
Weight: 3,74 kg	
Noise classification: Class 1 (very slight noise, suitable for sensitive environments)	r noise-
Legal specifications	
Special product: Not designed for household room illu	mination
Intended use: Show effect lighting	