

## EUROLITE LED THA-100F MK3 Theater-Spot

Fresnel spotlight (fresnel lens), 100 W warm white LED, CRI >90, quiet, DMX

Art. No.: 41602127

GTIN: 4026397690453



**List price: 653.31 €**

incl. 19% VAT.

### Features:

- 1 powerful LED 100 W COB (chip-on-board) warm white (WW)
  - Strobe effect
  - The device is cooled by low-noise cooling fan
  - Control via stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
  - Flicker-free
  - With a beam angle of 8° - 55°
  - Very high color rendering index (CRI)
  - With Mounting bracket
  - LCD display
  - Dimmer electronic; dimmer curves with adjustable response; pulse-width modulation variable; Dimmer speed (step response) adjustable
  - Preprogrammed in Light Captain
  - Rubber feet
  - Mains input and output for power linking up to 8 units
  - For application areas such as: Trade fair and shop fitting; Installation; Stage; theater
  - Very quiet working noise
  - Application possibility: Suspended; on stand
- Package contents**
- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x barndoor, 1 x filter frame

### Logistic

EAN / GTIN: 4026397690453

Weight: 9,30 kg

Length: 0.49 m

Width: 0.40 m

Height: 0.38 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	95 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version
Cable length:	Approx. 1,1 m
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 2 A Fuse replaceable
Lamp type:	LED lamp
LED:	1 x 100 W COB (chip-on-board) warm white (WW)
Color temperature:	3000K
Flash rate:	20 Hz
DMX channels:	1; 3
DMX input:	3-pin XLR (M) mounting version 5-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version 5-pin XLR (F) mounting version
Cooling:	Low-noise cooling fan
Control:	Stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light Captain
Projection:	Flicker-free
Beam angle:	8° - 55°
Beam angle (1/2 peak):	8 - 40°
Beam angle (1/10 peak):	16 - 55°
Color rendering index (CRI):	96 Ra
Luminous flux:	5384 lm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Transport aid:	Rubber feet
Dimensions:	Length: 35,0 cm Width: 31,5 cm Height: 39,5 cm
Weight:	7,15 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Energy efficiency class (A - G):	G