

EUROLITE LED THA-120PC Theater-Spot

Fresnel spotlight (fresnel lens), 120 W COB LED (RGBW), extremely quiet, DMX

Art. No.: 41602130

GTIN: 4026397578447



List price: 653.31 €

incl. 19% VAT.

Features:

- Equipped with one 120 W COB LED in the colors red, green, blue and white
- Manual, stepless zoom
- Dimmer speed (step response) adjustable
- Addressing and setting via Control Board with LCD and four operating buttons
- Functions: RGBW color mixture, automatic color change, internal programs, dimmer, strobe effects, sound-control via built-in microphone
- Speed of color changes and strobe effects programmable
- Mounting bracket for installation on a stand or a crossbeam
- Locking possibility at the bracket
- With color filter frame
- Optional barndoors available
- Small and robust spot with metal housing
- Neutrik powerCON terminals for power linking up to 8 units
- LED: 1 x COB (chip-on-board) 120 W 4in1 QCL RGBW (homogenous color mix)
- Can be operated in 4; 6; 7 CH mode
- The device is cooled by temperature-controlled fan
- Controlling by Stand-alone; DMX; Sound to light via Microphone
- Is in EUROLITE LED PC-Control 512 software; Light J Software; EASY SHOW; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE already preprogrammed
- Flicker-free projection

Logistic

EAN / GTIN: 4026397578447

Weight: 6,60 kg

Length: 0.49 m

Width: 0.32 m

Height: 0.32 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	135 W
IP classification:	IP20
Power connection:	Mains input PowerCON (blue), mounting version Power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
LED:	1 x COB (chip-on-board) 120 W 4in1 QCL RGBW (homogenous color mix)
DMX channels:	4; 6; 7
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; Sound to light via Microphone; EUROLITE LED PC-Control 512 software; Light J Software; EASY SHOW; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE
Beam angle:	3 - 43°
Beam angle (1/2 peak):	3 - 32°
Beam angle (1/10 peak):	9 - 43°
Housing color:	Black
Dimensions:	Length: 37 cm Width: 25,6 cm Depth: 36 cm
Weight:	5,85 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Special product:	Not designed for household room illumination
intended use:	show effect lighting