

EUROLITE LED THA-250F 2700K-6500K Theater Spot

Fresnel spotlight, 250 W LED, variable color temperature, CRI >90, zoom

Art. No.: 41602135

GTIN: 4026397610833

The article is no longer in our assortment.

Features:

- 1 powerful LED 250 W COB (chip-on-board) 2in1 BCL CW/WW (homogenous color mix)
- Variable color temperature 2700 K - 6500 K
- Zoom motor driven; focus manual
- Strobe effect
- The device is cooled by temperature-controlled fan
- Control via DMX
- Flicker-free
- With a beam angle of 6° - 46°
- Very high color rendering index (CRI)
- With mounting bracket
- LCD display
- Dimmer electronic
- Preprogrammed in LED PC-Control 512; Light´J; Light Captain
- Mains input and output for power linking up to 8 units

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x barndoor, 1 x XLR cable, 1 x plug (male)

Logistic

EAN / GTIN: 4026397610833

Weight: 11,50 kg

Length: 0.52 m

Width: 0.33 m

Height: 0.32 m

Technical specifications:

| | |
|---------------|------------------------|
| Power supply: | 100-240 V AC, 50/60 Hz |
|---------------|------------------------|

| | |
|--------------------|-------|
| Power consumption: | 200 W |
|--------------------|-------|

| | |
|--------------------|------|
| IP classification: | IP20 |
|--------------------|------|

| | |
|------------------------------|---|
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x P-Con (gray), mounting version |
| Lamp type: | LED lamp |
| LED type: | 1 x 250 W COB (chip-on-board) 2in1 BCL CW/WW (homogenous color mix) |
| Equipment: | Zoom motor driven; focus manual |
| DMX channels: | 4; 5 |
| DMX input: | 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version |
| Cooling: | Temperature-controlled fan |
| Control: | DMX |
| Preprogrammed in: | LED PC-Control 512; Light'J; Light Captain |
| Projection: | Flicker-free |
| Beam angle: | 6° - 46° |
| Beam angle (1/2 peak): | 6 - 25° |
| Beam angle (1/10 peak): | 20 - 46° |
| Color temperature: | 2700K - 6500K adjustable |
| Color rendering index (CRI): | 96 Ra |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Display type: | LCD display |
| Dimensions: | Length: 43,5 cm Width: 27,5 cm Height: 38,5 cm |
| Weight: | 10,45 kg |
| Noise classification: | Class 2 (slight noise) |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |