

# **EUROLITE LED THA-350F WW/CW Theater Spot**

Fresnel spotlight, 350 W LED, variable color temperature, CRI >90, zoom

Art. No.: 41602136 GTIN: 4026397718126









List price: 1307.81 €

incl. 19% VAT.

#### Features:

- Temperature-protected handle
- 1 powerful LED 350 W COB (chip-on-board) 2in1 BCL CW/WW (homogenous color mix)
- Variable color temperature 2700 K 6500 K
- The device is cooled by temperature-controlled fan
- Control via stand-alone; master/slave function; DMX
- Flicker-free
- Strobe effect
- With a beam angle of 11° 41°
- Very high color rendering index (CRI)
- With mounting bracket
- LCD display
- Zoom motor driven
- Dimmer electronic
- Preprogrammed in Light Captain
- Mains input and output for power linking up to 8 units
- Very quiet working noise
- For application areas such as: Trade fair and shop fitting; installation; stage; theater
- Application possibility: Suspended; on stand

#### Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x XLR cable, 1 x plug (male), 1 x barndoor

### **Technical specifications:**

Power supply:

100-240 V AC, 50/60 Hz

## Logistic

EAN / GTIN: 4026397718126

Weight: 11,80 kg Length: 0.52 m Width: 0.33 m Heigth: 0.32 m

Power consumption:	280 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 3,15 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 350 W COB (chip-on-board) 2in1 BCL CW/WW (homogenous color mix)
Equipment:	Zoom motor driven
DMX channels:	4; 5
DMX input:	3-pin XLR (M) mounting version 5-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; master/slave function; DMX
Preprogrammed in:	Light Captain
Projection:	Flicker-free
Beam angle:	11° - 41°
Beam angle (1/2 peak):	11 - 27°
Beam angle (1/10 peak):	22 - 41°
Color temperature:	2700K - 6500K adjustable
Color rendering index (CRI):	95 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Dimensions:	Length: 43,5 cm Width: 28,5 cm Height: 38,5 cm
Weight:	10,50 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting