

EUROLITE LED THA-450F Theater-Spot

Fresnel spotlight (fresnel lens), 440 W RGLB LED, quiet, DMX

Art. No.: 41602200

GTIN: 4026397713954



List price: 1664.81 €

incl. 19% VAT.

Features:

- Rugged metal housing
- Rubber-coated handle
- 1 powerful LED 450 W COB (chip-on-board) 4in1 QCL RGLB
- Variable color temperature 2400 K - 8500 K
- Exact 16 bit resolution at Dimmer
- Zoom motor-driven; Zoom manual
- Color blend stepless; dimmer curves with adjustable response; Dimmer electronic; pulse-width modulation variable; Dimmer speed (step response) adjustable
- Strobe effect
- Direct color selection for 117 preset colors
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; RDM; Rotary dial for brightness; QuickDMX via USB (optional); CRMX by LumenRadio (optional); W-DMX by wireless solution (optional)
- Preprogrammed in Light Captain
- With a beam angle of 5° - 50°
- Very high color rendering index (CRI)
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles
- LCD display
- Very quiet working noise
- For application areas such as: Trade fair and shop fitting; Installation; Stage; theater
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x barndoor, 1 x filter frame

Logistic

EAN / GTIN: 4026397713954

Weight: 12,10 kg

Length: 0.56 m

Width: 0.41 m

Height: 0.40 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	440 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (gray), mounting version
Fuse:	T 3 A Fuse replaceable
LED:	1 x 450 W COB (chip-on-board) 4in1 QCL RGBL
Color temperature:	2400K - 8500K adjustable
Equipment:	Zoom motor-driven; Zoom manual
DMX channels:	1; 2; 4; 7; 18
DMX input:	3-pin XLR (M) mounting version 5-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; RDM; Rotary dial for brightness; QuickDMX via USB (optional); CRMX by LumenRadio (optional); W-DMX by wireless solution (optional)
Preprogrammed in:	Light Captain
Beam angle:	5° - 50°
Beam angle (1/2 peak):	5 - 40°
Beam angle (1/10 peak):	14 - 50°
Color rendering index (CRI):	91 Ra
Housing color:	Black
Attachment system:	Panning and tilting mounting bracket for ceiling or wall installation in most varying angles
Display type:	LCD display
Dimensions:	Length: 37,0 cm Width: 33,9 cm Height: 39,9 cm
Weight:	9,45 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting