

EUROLITE LED PML-30 CW/WW

Fanless LED spotlight with 30 W white light LED, color rendering index (CRI) > 90 and frost filter


Art. No.: 41602590 GTIN: 4026397715002











incl. 19% VAT.

Features:

- Additional frost filter provides a wide, soft and homogeneous light
- Compact design
- 1 powerful LED 30 W COB (chip-on-board) 2in1 BCL CW/WW (homogenous color mix)
- Variable color temperature 2900 K 5900 K
- Direct color selection
- The device is cooled by passive convection cooling
- Control via stand-alone; quick select potentiometer for brightness and color temperature
- Flicker-free
- With a beam angle of 20°
- Very high color rendering index (CRI)
- With double bracket
- Dimmer electronic
- Mains input and output for power linking up to 8 units
- For application areas such as: Trade fair and shop fitting; installation; mobile use; video and photography
- Silent operation
- Application possibility: Standing; suspended; on stand

Package contents

1 x spotlight, 1 x user manual, 1 x power cord, 1 x frost filter

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	35 W

Logistic

EAN / GTIN: 4026397715002

Weight: 2,12 kg Length: 0.19 m Width: 0.17 m Heigth: 0.28 m

IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	1 x 30 W COB (chip-on-board) 2in1 BCL CW/WW (homogenous color mix)
Cooling:	Passive convection cooling
Control:	Stand-alone; quick select potentiometer for brightness and color temperature
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20°
	Frost filter 30°
Beam angle (1/10 peak):	40°
Color temperature:	2900K - 5900K adjustable
Color rendering index (CRI):	90 Ra
Illuminance in Lux (lx):	Narrow cold white (CW) 1m: 14257 lx, 3m: 1387 lx, 6m: 351 lx
	Narrow warm white (WW) 1m: 11413 lx, 3m: 1109 lx, 6m: 281 lx
	Wide warm white (WW) 1m: 7289 lx, 3m: 697 lx, 6m: 175 lx
	Wide cold white (CW) 1m: 9107 lx, 3m: 872 lx, 6m: 218 lx
Housing color:	Black
Attachment system:	Double bracket
Dimensions:	Length: 12 cm
	Width: 17,4 cm
	Height: 22,5 cm
Weight:	1,89 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting