

EUROLITE LED PML-80 COB RGB 80W Spot/Wash

Spotlight with 80 W COB LED (RGB), beam angle 16°/36° (lens)

Art. No.: 41602595

GTIN: 4026397572599



List price: 296.31 €

incl. 19% VAT.

Features:

- Interchangeable front lens for 16° or 36° beam angle
- In color change operation suitable for continuous use
- Compact design
- 1 powerful LED 80 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
- Strobe effect
- The device is cooled by passive convection cooling
- Control via DMX; sound to light via microphone
- Flicker-free
- With a beam angle of 16°
- With double bracket
- 4 digit 7-segment LED display
- Color blend stepless; color change adjustable; colors preset; Dimmer electronic; Dimmer speed (step response) adjustable
- Silent operation
- Preprogrammed in LED PC-Control 512; Light´J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; installation; theater
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x beamshaper

Logistic

EAN / GTIN: 4026397572599

Weight: 2,31 kg

Length: 0.30 m

Width: 0.18 m

Height: 0.18 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	65 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	1 x 80 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
DMX channels:	3; 5; 6; 7; 8
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; sound to light via microphone
Preprogrammed in:	LED PC-Control 512; Light´J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	16°
Beam angle (1/2 peak):	Spot 16° Wash effect 36°
Beam angle (1/10 peak):	Spot 28° Wash effect 78°
Housing color:	Black
Attachment system:	Double bracket Double bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 17,5 cm Depth: 25,7 cm Height: 16,9 cm
Weight:	2,04 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting