EUROLITE LED PAR-64 COB 3000K 100W Zoom wh

PAR spot with warm white 100 W COB LED and manual zoom

Art. No.: 41603602

GTIN: 4026397694826

List price: 355.81 €

incl. 19% VAT.

Features:

- Light performance comparable to a traditional 1000 W halogen spot light
- Homogeneous light distribution
- 1 powerful LED 100 W COB (chip-on-board) warm white (WW)
- The device is cooled by cooling fan
- Control via DMX
- Flicker-free
- Very high color rendering index (CRI)
- With Mounting bracket
- 4 digit 7-segment LED display
- For application areas such as: Theater; Trade fair and shop fitting; Stage; Wedding/gala/events
- Dimmer speed (step response) adjustable; pulse-width modulation variable; Gamma correction adjustable
- Strobe effect
- Preprogrammed in Light Captain; Light´J
- Mains input and output for power linking up to 8 units
- Application possibility: Suspended; on stand

  Package contents
- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x xLR cable, 1 x filter frame, 1 x mounting bracket, 2 x knurled screw, 2 x washer

Logistic

EAN / GTIN: 4026397694826

Weight: 4,80 kg

Length: 0.50 m

Width: 0.38 m

Heigth: 0.38 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	110 W

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	1 x 100 W COB (chip-on-board) warm white (WW)
DMX channels:	1; 2; 3
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX
Preprogrammed in:	Light Captain; Light´J
Projection:	Flicker-free
Beam angle (1/10 peak):	15 - 48°
Color temperature:	3000K
Color rendering index (CRI):	90 Ra
Illuminance in Lux (lx):	Narrow warm white (WW) 3m: 14535 lx, 6m: 3666 lx Wide warm white (WW) 3m: 2134 lx, 6m: 614 lx
Housing color:	White
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 26 cm Depth: 43,5 cm Height: 37,5 cm
Weight:	3,80 kg
Noise classification:	Class 2 (slight noise)

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.