

EUROLITE LED PAR-64 COB RGBW 120W Zoom bk

PAR spot with 120 W RGBW LED and manual zoom

Art. No.: 41603605

GTIN: 4026397657616



The article is no longer in our assortment.

Description:

PAR spotlight with 120 watt RGBW LED and manual zoom

The EUROLITE LED PAR-64 COB is equipped with a powerful 120 W LED (COB) in red, green, blue and white (RGBW). It is ideal for your lighting installation. Thanks to its adjustable PWM frequency, its projection is flicker-free - the spotlight is also suitable for video recording.

The beam angle is manually adjustable from 11° to 35°.

Choose from different dimmer curves and speeds - according to your needs.

Control is via DMX or in stand-alone mode. In auto and music mode you can play three integrated show programs.

You can address and adjust your PAR spotlight via the integrated control unit with 4-digit LED display.

The P-Con connections make it easy to connect up to eight devices together.

Features:

- 1 powerful LED 120 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- 3 integrated show programs
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; Sound to light via Microphone; Master/slave function
- Flicker-free
- With a beam angle of 11° - 48°
- With Mounting bracket
- For application areas such as: Stage
- Color blend stepless; dimmer curves with adjustable response; pulse-width modulation variable

Logistic

EAN / GTIN: 4026397657616

Weight: 5,00 kg

Length: 0.49 m

Width: 0.37 m

Height: 0.37 m

- Preprogrammed in LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light´J; Light Captain; EASY SHOW 2; EASY SHOW 3
- Mains input and output for power linking up to 8 units

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x xLR cable, 1 x filter frame, 1 x mounting bracket, 2 x knurled screw, 2 x washer

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	140 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	F 2 A
Lamp type:	LED lamp
LED:	1 x 120 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 4; 5; 9; 6
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; Sound to light via Microphone; Master/slave function
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light´J; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	11° - 48°
Beam angle (1/2 peak):	11 - 35°
Beam angle (1/10 peak):	15 - 48°
Housing color:	Black
Attachment system:	Mounting bracket
Dimensions:	Width: 26 cm Depth: 43,5 cm Height: 37,5 cm
Weight:	3,90 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting