eurolite®

EUROLITE LED PAR-64 COB RGBW 120W Zoom bk MK2

PAR spot with 120 W RGBW LED and manual zoom

Art. No.: 41603606 GTIN: 4026397718003









List price: 534.31 €

incl. 19% VAT.

Features:

- Improved version with more light output than predecessor model
- 1 powerful LED 120 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- 3 integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; Light Captain; Colorchief
- Flicker-free
- With a beam angle of 11° 48°
- With mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; installation; rental; clubs/dancing school
- Application possibility: Suspended; on stand
- Package contents
- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x XLR cable, 1 x filter frame

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	140 W
IP classification:	IP20
Protection class:	Protection class I

Logistic

EAN / GTIN: 4026397718003 Weight: 4,75 kg Length: 0.49 m Width: 0.38 m Heigth: 0.38 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	F 2 A
Lamp type:	LED lamp
LED type:	1 x 120 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 4; 5; 9; 6
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light'J; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	11° - 48°
Beam angle (1/2 peak):	11 - 35°
Beam angle (1/10 peak):	15 - 48°
Housing color:	Black
Attachment system:	Mounting bracket
Dimensions:	Width: 26 cm
	Depth: 43,5 cm
	Height: 37,5 cm
Weight:	3,70 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting