eurolite®

EUROLITE LED ML-56 COB 5600K 100W 60° bk

LED spot in Multi Lens design with powerful white LED

The article is no longer in our assortment.

Features:

- Equipped with one 100 W COB LED
- Functions: dimmer, strobe effect, Master/Slave operation
- Operable in stand-alone mode or via DMX
- 1 or 3 DMX channels selectable for numerous applications
- Beam angle approximately 60°
- Different dimmer curves and dimmer speed adjustable
- 5600 K color temperature
- Mounting bracket for installations on a stand or a crossbeam
- Locking possibility at the mounting bracket
- Comfortable addressing and setting via Control Board with LCD display and four operating buttons
- Ready for connection with power cord and safety plug
- With color filter frame
- Optional barndoors available
- Ideal for theatres, large stages as pre-stage spot and mobile use
- Available in silver or in black

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	120,00 W
Dimensions:	Width: 30 cm
	Depth: 31 cm

Logistic

EAN / GTIN: 4026397457346 Weight: 4,75 kg Length: 0.28 m Width: 0.27 m Heigth: 0.38 m

Art. No.: 41604020 GTIN: 4026397457346









Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

	Height: 24 cm
Weight:	4,40 kg
DMX channels:	1/3
DMX connection:	3-pin XLR
LED type:	Array Cluster 100 W, white
LED number:	1
Color temperature:	5600 K
Beam angle:	60°
Dimensions (L x W x H):	240 x 300 x 310 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting