

EUROLITE Audience Blinder 2x50W LED COB 3200K

PRO audience blinder with 2 x 50 W COB LED

Art. No.: 41606100 GTIN: 4026397458176



The article is no longer in our assortment.

Features:

- 3200 K color temperature
- 1, 2 or 4 DMX channels selectable for various applications
- Each LED can be controlled individually
- Functions: strobe effect with variable speed, dimmer, Master/Slave
- Different dimmer curves and dimmer speed adjustable
- DMX-controlled operation or stand-alone operation with Master/Slave function
- For use on stages, catwalks and crossbeam systems
- Comfortable addressing and setting via control panel with LC display and four operating buttons
- Locking possibility at the mounting bracket
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller
- Preprogrammed in Light'J; LED PC-Control 512; Light Captain

Technical specifications:

Power supply:	230 V AC, 50 Hz	
Power consumption:	120 W	
IP classification:	IP20	_
Flash rate:	1 - 20 Hz	
DMX channels:	2; 1	

Logistic

EAN / GTIN: 4026397458176

Weight: 4,65 kg Length: 0.46 m Width: 0.20 m Heigth: 0.30 m

Preprogrammed in:	Light´J; LED PC-Control 512; Light Captain
Beam angle (1/2 peak):	60°
Color temperature:	3200K
Dimensions:	Width: 42 cm
	Depth: 24 cm
	Height: 14 cm
Weight:	4,10 kg
DMX channels:	1/2/4
DMX connection:	5-pin and 3-pin XLR
Flash-rate:	20 Hz
LED number:	2
LED type:	Array 50 W, white
Color temperature:	3200 K
Beam angle:	60°
Dimensions (L x W x H):	140 x 420 x 240 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting