

EUROLITE Multiflood IP 8x10W RGBW Wash

Silent IP65 LED floodlight with RGBW color mixing, diffuser cover, barn doors and IR remote control

Art. No.: 41606250

GTIN: 4026397724196



List price: 510.51 €

incl. 19% VAT.

Features:

- Silent operation
- Control via stand-alone; DMX; master/slave function; IR remote control; RDM
- Additional frost filter provides a wide, soft and homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- 8 powerful LEDs 10 W high-power 4in1 QCL RGBW (homogenous color mix)
- 36 integrated show programs
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) with adjustable response; white balance
- Strobe effect
- 3 buttons on the remote control for saving your own settings
- With a beam angle of 10°
- With mounting bracket; with omega bracket
- OLED display
- Flicker-free
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- With pressure compensation membrane
- With a KENSINGTON LOCK theft protection
- For application areas such as: Stage; architecture; mobile use; rental
- The device is cooled by passive convection cooling
- Preprogrammed in Light Captain; LED PC-Control 512; Light´J; Colorchief
- Application possibility: Suspended; on stand; standing

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x remote control, 1 x frost filter, 1 x omega bracket, 1 x barn door, 1 x battery

Logistic

EAN / GTIN: 4026397724196

Weight: 7,10 kg

Length: 0.36 m

Width: 0.27 m

Height: 0.30 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	80 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	8 x 10 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; master/slave function; IR remote control; RDM
Preprogrammed in:	Light Captain; LED PC-Control 512; Light´J; Colorchief
Projection:	Flicker-free
Beam angle:	10°
Beam angle (1/2 peak):	10° Frost filter 25°
Beam angle (1/10 peak):	25° Frost filter 55°
Housing color:	Black
Attachment system:	Mounting bracket Omega bracket
Display type:	OLED display
Theft protection:	KENSINGTON LOCK
Dimensions:	Length: 31,9 cm Width: 14 cm Height: 24,8 cm
Weight:	6,10 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting