

EUROLITE Multiflood IP 18x10W RGBW Wash CRMX

Art. No.: 41606260

Silent IP65 LED floodlight with RGBW color mixing, CRMX, diffuser cover, barn doors, IR remote control GTIN: 4026397732610

List price: 891.31 €

incl. 19% VAT.

Features:

- Integrated wireless receiver for CRMX operation
- Silent operation
- Control via DMX; W-DMX by wireless solution; CRMX by LumenRadio; master/slave function; RDM; stand-alone; IR remote control
- Additional frost filter provides a wide, soft and homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- 18 powerful LEDs 10 W high-power 4in1 QCL RGBW (homogenous color mix)
- 3 buttons on the remote control for saving your own settings
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) with adjustable response; white balance
- Direct color selection for 15 preset colors
- 36 integrated show programs
- Strobe effect
- Flicker-free
- With a beam angle of 10°
- With mounting bracket; with omega bracket
- OLED display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use
- With pressure compensation membrane
- With a KENSINGTON LOCK theft protection
- For application areas such as: Stage; architecture; mobile use; rental
- The device is cooled by passive convection cooling
- Application possibility: Suspended; on stand; standing
- Preprogrammed in Light´J; Light Captain; Colorchief

Package contents

Logistic

EAN / GTIN: 4026397732610

Weight: 12,00 kg

Length: 0.46 m

Width: 0.34 m

Height: 0.37 m

- 1 x device, 1 x user manual, 1 x power cord, 1 x declaration of conformity, 1 x frost filter, 1 x barndoor, 1 x omega bracket, 1 x remote control

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	170 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	1 x IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	18 x 10 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	1 x 3-pin XLR (M) mounting version IP 1 x 5-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP 1 x 5-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	DMX; W-DMX by wireless solution; CRMX by LumenRadio; master/slave function; RDM; stand- alone; IR remote control
Preprogrammed in:	Light´J; Light Captain; Colorchief
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	10°
Beam angle (1/2 peak):	10° Frost filter 20°
Beam angle (1/10 peak):	25° Frost filter 50°
Housing color:	Black
Attachment system:	Mounting bracket Omega bracket
Display type:	OLED display
Theft protection:	KENSINGTON LOCK
Dimensions:	Length: 41 cm Width: 18,4 cm Height: 26,9 cm
Weight:	10,00 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination

Intended use:

Show effect lighting