

EUROLITE AKKU Multiflood IP 18x10W RGBW Wash CRMX

Art. No.: 41606265

Silent battery-powered IP65 floodlight with RGBW LEDs, CRMX, diffuser cover, barn doors, IR remote control

GTIN: 4026397732467

List price: 1367.31 €

incl. 19% VAT.

Features:

- Cordless, flexible and versatile
- Silent operation
- Control via IR remote control; W-DMX by wireless solution; stand-alone; CRMX by LumenRadio; DMX; RDM; master/slave function
- Integrated wireless receiver for CRMX operation
- Additional frost filter provides a wide, soft and homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- 18 powerful LEDs 10 W high-power 4in1 QCL RGBW (homogenous color mix)
- 3 buttons on the remote control for saving your own settings
- Emergency lighting function in case of power failure; color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) with adjustable response; white balance
- 36 integrated show programs
- Strobe effect
- With a beam angle of 10°
- Flicker-free
- The device is cooled by passive convection cooling
- With mounting bracket; with omega bracket
- OLED display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use
- With pressure compensation membrane
- With a KENSINGTON LOCK theft protection
- For application areas such as: Stage; architecture; mobile use; rental
- Battery operation up to 5,5h depending on program used
- Direct color selection for 15 preset colors

Logistic

EAN / GTIN: 4026397732467

Weight: 13,90 kg

Length: 0.46 m

Width: 0.34 m

Height: 0.37 m

- Display of the remaining battery life for the current setting
- Charge status indicator
- Application possibility: Suspended; on stand; standing
- Preprogrammed in Light´J; Light Captain; Colorchief

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x declaration of conformity, 1 x frost filter, 1 x barndoor, 1 x omega bracket, 1 x remote control

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug Battery/battery pack
Power output:	1 x IP T-Con (F) mounting version
Battery pack type:	1 x lithium ion 29,6 V, 12,5 mAh, 370 Wh
Battery pack:	Battery operation up to 5,5h depending on program used Recharging time 2,5h
Lamp type:	LED lamp
LED type:	18 x 10 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	1 x 3-pin XLR (F) mounting version IP 1 x 5-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP 1 x 5-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	IR remote control; W-DMX by wireless solution; stand-alone; CRMX by LumenRadio; DMX; RDM; master/slave function
Preprogrammed in:	Light´J; Light Captain; Colorchief
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	10°
Beam angle (1/2 peak):	10° Frost filter 40°
Beam angle (1/10 peak):	25°
Housing color:	Black
Attachment system:	Mounting bracket Omega bracket
Display type:	OLED display
Display:	Battery runtime calculation , charge status indicator
Theft protection:	KENSINGTON LOCK
Dimensions:	Length: 41 cm Width: 18,4 cm

	Height: 26,9 cm
Weight:	12,05 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting