

EUROLITE LED PAR-20 3CT bi

LED spotlight with three adjustable color temperatures and high color rendering index

Art. No.: 41607021

GTIN: 4026397692075



List price: 77.23 €

incl. 19% VAT.

Features:

- 1 powerful LED 16 W COB (chip-on-board) 2in1 BCL CW/WW
 - The device is cooled by passive convection cooling
 - Control via stand-alone
 - Flicker-free
 - With a beam angle of 25°
 - Very high color rendering index (CRI)
 - With Mounting bracket
 - Available in various colors
 - Silent operation
 - For application areas such as: Trade fair and shop fitting; video and photography; Installation; restaurants, bars and hotels
 - Dimmable
 - Direct color temperature selection for 3 preset values
 - Dimmer electronic
 - Application possibility: Suspended; on stand
- Package contents**
- 1 x spotlight, 1 x filter frame, 1 x user manual

Logistic

EAN / GTIN: 4026397692075

Weight: 0,57 kg

Length: 0.10 m

Width: 0.10 m

Height: 0.24 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: Max. 12 W

IP classification: IP20

| | |
|----------------------------------|---|
| Protection class: | Protection class I |
| Power connection: | Fixed power supply cord with safety plug |
| Cable length: | Approx. 0,4 m |
| Lamp type: | LED lamp |
| Lamp specification: | Dimmable |
| LED: | 1 x 16 W COB (chip-on-board) 2in1 BCL CW/WW |
| Color temperature: | 3000K; 4000K; 5000K |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone |
| Projection: | Flicker-free |
| Beam angle: | 25° |
| Beam angle (1/2 peak): | 25° |
| Beam angle (1/10 peak): | 50° |
| Color rendering index (CRI): | 90 Ra |
| Illuminance in Lux (lx): | 3000 K 1m: 2463 lx, 3m: 300 lx, 6m: 79 lx 4000 K 1m: 2148 lx, 3m: 315 lx, 6m: 86 lx 5000 K 1m: 2576 lx, 3m: 346 lx, 6m: 93 lx |
| Lamp life: | 15000 h |
| Luminous flux: | 800 lm |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Material: | Aluminum |
| Slot for spot length: | 8,6 cm x 8,6 cm |
| Dimensions: | Length: 19,2 cm Width: 11,5 cm Height: 16,0 cm |
| Weight: | 520 g |
| Noise classification: | Class 0 (no noise at all) |
| Energy efficiency class (A - G): | G |
| Mounting bracket | |
| Diameter mounting holes: | 2 x Ø10mm |
| Material: | Aluminum, 3 mm |
| Dimensions: | Width: 9,4 cm Depth: 2 cm Height: 12,4 cm |
| Filter frame | |
| Shape: | Octagonal |
| Material: | Aluminum |
| Dimensions: | Width: 8,3 cm Height: 8,3 cm Diameter: Ø 6,1 cm |