

EUROLITE LED PAR-30 3CT sil

LED spotlight with three adjustable color temperatures and high color rendering index

Art. No.: 41607051

GTIN: 4026397692129



List price: 89.13 €

incl. 19% VAT.

Features:

- 1 powerful LED 16 W COB (chip-on-board) 2in1 BCL CW/WW
- The device is cooled by passive convection cooling
- Control via Quick select potentiometer for brightness and color temperature
- Flicker-free
- With a beam angle of 20°
- Very high color rendering index (CRI)
- With Mounting bracket
- Available in various colors
- Silent operation
- For application areas such as: Trade fair and shop fitting; video and photography; Installation; restaurants, bars and hotels
- Dimmable
- Direct color temperature selection for 3 preset values
- Dimmer electronic
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x filter frame, 1 x user manual

Logistic

EAN / GTIN: 4026397692129

Weight: 0,87 kg

Length: 0.14 m

Width: 0.14 m

Height: 0.27 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: Max. 18,5 W

IP classification: IP20

| | |
|----------------------------------|--|
| Protection class: | Protection class I |
| Power connection: | Fixed power supply cord with safety plug |
| Cable length: | Approx. 0,4 m |
| Lamp type: | LED lamp |
| Lamp specification: | Dimmable |
| LED: | 1 x 16 W COB (chip-on-board) 2in1 BCL CW/WW |
| Color temperature: | 3000K; 4000K; 5000K |
| Cooling: | Passive convection cooling |
| Control: | Quick select potentiometer for brightness and color temperature |
| Projection: | Flicker-free |
| Beam angle: | 20° |
| Beam angle (1/2 peak): | 20° |
| Beam angle (1/10 peak): | 35° |
| Color rendering index (CRI): | 90 Ra |
| Illuminance in Lux (lx): | 3000 K 1m: 4760 lx, 3m: 606 lx, 6m: 160 lx 4000 K 1m: 5248 lx, 3m: 631 lx, 6m: 175 lx 5000 K 1m: 5754 lx, 3m: 713 lx, 6m: 191 lx |
| Lamp life: | 15000 h |
| Luminous flux: | 1300 lm |
| Housing color: | Silver |
| Attachment system: | Mounting bracket |
| Material: | Aluminum |
| Slot for spot length: | 12,8 cm x 12,8 cm |
| Dimensions: | Length: 24 cm Width: 14,7 cm Height: 20 cm |
| Weight: | 800 g |
| Noise classification: | Class 0 (no noise at all) |
| Energy efficiency class (A - G): | G |
| Mounting bracket | |
| Diameter mounting holes: | 2 x Ø10mm |
| Material: | Aluminum, 3 mm |
| Dimensions: | Width: 13 cm Depth: 2 cm Height: 13 cm |
| Filter frame | |
| Shape: | Octagonal |
| Material: | Aluminum, 0,8 mm |
| Dimensions: | Width: 12,6 cm Height: 12,6 cm Diameter: Ø 9,4 cm |