

## EUROLITE LED PAR-56 COB RGB 25W bk

PAR spot with 25 W COB LED (RGB) & adjustable beam angle (60°/20°)

Art. No.: 41607215

GTIN: 4026397533941



**The article is no longer in our assortment.**

### Features:

- Equipped with one powerful 25 W COB LED with RGB colors
- Functions: stepless RGB color mixture, solid colors, built-in programs, dimmer, strobe effect, Master/Slave operation
- Dimmer speed (step response) adjustable
- Operable in stand-alone mode, via DMX interface or via IR remote control
- Controllable via IR remote control; included in the delivery
- Adjustable microphone sensitivity via Control Board
- Different beam angles (from approx. 60° to approx. 20°) possible via included lens
- Easy installation
- Ideal as floor spot via additional bracket
- Locking possibility at the brackets
- Comfortable addressing and setting via Control Board with LED display and three operating buttons
- Ready for connection via power cord with safety plug
- Switch-mode power supply for operation between 100 and 240 Volts
- Available in silver or black
- 1 powerful LED 25 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
- Strobe effect
- Control via stand-alone; DMX; sound to light via microphone
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE
- Flicker-free
- With a beam angle of 20°

### Package contents

- 1 x spotlight, 1 x remote control, 1 x user manual, 1 x lens, 1 x battery

### Logistic

EAN / GTIN: 4026397533941

Weight: 2,10 kg

Length: 0.21 m

Width: 0.21 m

Height: 0.31 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	25 W
IP classification:	IP20
Power connection:	Fixed power supply cord with safety plug
Lamp type:	LED lamp
LED type:	1 x 25 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
DMX channels:	3; 5
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	Stand-alone; DMX; sound to light via microphone
Preprogrammed in:	Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	With fresnell 20° 60°
Beam angle (1/10 peak):	With fresnell 28° 101°
Housing color:	Black
Dimensions:	Width: 22 cm Depth: 17 cm Height: 24,5 cm
Weight:	1,88 kg
Noise classification:	Class 2 (slight noise)
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting