Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

eurolite®

EUROLITE LED PAR-56 COB RGB 25W sil

PAR spot with 25 W COB LED (RGB) & adjustable beam angle (60°/20°)

The article is no longer in our assortment.

Features:

- Equipped with one powerful 25 W COB LED with RGB colors
- 3 or 5 DMX channels selectable
- Functions: stepless RGB color mixture, solid colors, built-in programs, dimmer, strobe effect, Master/Slave operation
- Dimmer speed (step response) adjustable
- Operable in stand-alone mode, via DMX interface or via IR remote control
- Controllable via IR remote control; included in the delivery
- Adjustable microphone sensitivity via Control Board
- Different beam angles (from approx. 60° to approx. 20°) possible via included lens
- Easy installation
- Ideal as floor spot via additional bracket
- Locking possibility at the brackets
- Comfortable addressing and setting via Control Board with LED display and three operating buttons
- Ready for connection via power cord with safety plug
- Switch-mode power supply for operation between 100 and 240 Volts
- Available in silver or black
- 1 powerful LED 25 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
- Strobe effect
- Control via IR remote control; stand-alone; DMX; Sound to light via Microphone
- Preprogrammed in LED PC-Control 512; Light'J; EASY SHOW 1
- Flicker-free
- With a beam angle of 20°
 Package contents
- 1 x remote control

Logistic

EAN / GTIN: 4026397533965 Weight: 2,10 kg Length: 0.21 m Width: 0.21 m Heigth: 0.31 m





Art. No.: 41607240 GTIN: 4026397533965







Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	25 W
IP classification:	IP20
Power connection:	Fixed power supply cord with safety plug
Lamp type:	LED lamp
LED:	1 x 25 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
DMX channels:	3; 5
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	IR remote control; stand-alone; DMX; Sound to light via Microphone
Preprogrammed in:	LED PC-Control 512; Light J; EASY SHOW 1
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	With fresnell 20°
	60°
Beam angle (1/10 peak):	With fresnell 28°
	100°
Housing color:	Silver
Dimensions:	Width: 17 cm
	Depth: 22 cm
	Height: 24,5 cm
Weight:	1,89 kg
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganes built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting