

## EUROLITE LED ML-46 COB RGBAW 50W Floor bk

ML spot with 50 W COB LED and RGBAW color mixing

Art. No.: 41607311

GTIN: 4026397541465



**The article is no longer in our assortment.**

### Features:

- Equipped with a 50 W LED with RGBAW colors
- HSV, 5, 7, 8 or 11 DMX channels selectable
- Functions: static colors, RGBAW color mixture, automatic color change, internal programs and user defined auto programs, user defined color presets, dimmer and strobe settings, power limitation
- Adjustable white balance
- Dimmer speed (step response) adjustable
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Color presets can be called up via DMX controller
- Strobe effect with adjustable speed
- Beam angle approximately 22°
- Comfortable addressing and setting via Control Board with LED display and four operating buttons
- Ideal as floor spot via additional bracket
- Locking possibility at the brackets
- Optional color filter frame and barndoors available
- Ready for connection with power cord and safety plug
- Switch-mode power supply for operation between 100 and 240 Volts
- Available in silver or in black
- 1 powerful LED 50 W COB (chip-on-board) 5in1 PCL RGBWA (homogenous color mix)
- Strobe effect
- Control via DMX; sound to light via microphone
- Preprogrammed in Light'J; LED PC-Control 512
- Flicker-free
- With a beam angle of 22°

### Package contents

### Logistic

EAN / GTIN: 4026397541465

Weight: 3,00 kg

Length: 0.26 m

Width: 0.26 m

Height: 0.31 m

- 1 x filter frame

## Technical specifications:

Power consumption:	60 W
IP classification:	IP20
Power connection:	Fixed power supply cord with safety plug
Lamp type:	LED lamp
LED type:	1 x 50 W COB (chip-on-board) 5in1 PCL RGBWA (homogenous color mix)
Flash rate:	0 - 17 Hz
DMX channels:	5; 7; 8; 11; 3 (HSV hue/saturation/value)
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; sound to light via microphone
Preprogrammed in:	Light´J; LED PC-Control 512
Projection:	Flicker-free
Beam angle:	22°
Beam angle (1/2 peak):	22°
Beam angle (1/10 peak):	52°
Housing color:	Black
Dimensions:	Width: 23,5 cm Depth: 22 cm Height: 23 cm
Weight:	2,50 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting