

EUROLITE LED ML-56 COB RGBAW 100W Floor sil

ML spot with 100 W COB LED and RGBAW color mixing

Art. No.: 41607330

GTIN: 4026397529616



The article is no longer in our assortment.

Features:

- Equipped with a 100 W LED with RGBAW colors
- HSV, 5, 7, 8 or 11 DMX channels selectable
- Functions: static colors, RGBAW color mixture, automatic color change, internal programs and user defined auto programs, user defined color presets, dimmer and strobe settings, power limitation
- Adjustable white balance
- Dimmer speed (step response) adjustable
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Color presets can be called up via DMX controller
- Strobe effect with adjustable speed
- Beam angle approximately 39°
- Comfortable addressing and setting via Control Board with LED display and four operating buttons
- Ideal as floor spot via additional bracket
- Locking possibility at the brackets
- With color filter frame
- Optional barndoors available
- Ready for connection with power cord and safety plug
- Switch-mode power supply for operation between 100 and 240 Volts
- Available in silver or in black
- 1 powerful LED 100 W COB (chip-on-board) 5in1 PCL RGBWA (homogenous color mix)
- Strobe effect
- Control via DMX; Sound to light via Microphone
- Preprogrammed in Light'J; LED PC-Control 512
- Flicker-free
- With a beam angle of 39°

Logistic

EAN / GTIN: 4026397529616

Weight: 4,15 kg

Length: 0.29 m

Width: 0.29 m

Height: 0.39 m

Package contents

- 1 x filter frame

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	100 W
IP classification:	IP20
Power connection:	Fixed power supply cord with safety plug
Lamp type:	LED lamp
LED:	1 x 100 W COB (chip-on-board) 5in1 PCL RGBWA (homogenous color mix)
Flash rate:	0 - 17 Hz
DMX channels:	3 (HSV hue/saturation/value); 5; 7; 8; 11
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; Sound to light via Microphone
Preprogrammed in:	Light'J; LED PC-Control 512
Projection:	Flicker-free
Beam angle:	39°
Beam angle (1/2 peak):	39°
Beam angle (1/10 peak):	82°
Housing color:	Silver
Dimensions:	Width: 29 cm Depth: 25,5 cm Height: 32 cm
Weight:	3,55 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting