

EUROLITE AKKU Flat Light 1 sil

Flat spotlight with 15 W RGBW LED, QuickDMX transceiver and bracket

Art. No.: 41700001

GTIN: 4026397601367



Features:

- With QuickDMX transceiver - cordless, flexible and versatile
 - Equipped with a 15 W QCL LED in red, green, blue and white
 - Cordless and versatile
 - Elegant housing for indoor use
 - With integrated QuickDMX transmitter/receiver for the wireless transmission of DMX512 signals
 - Operation via built-in rechargeable lithium-ion battery with up to 18 hours operating time
 - Integrated automatic charging of the battery with indicator
 - Stepless color blend, color change, preset colors, dimmer and strobe effect
 - Dimmer speed (step response) adjustable
 - Addressing and setting via Control Board with touch buttons and LCD
 - Inclination angle manually adjustable via the bracket
 - Charger included in delivery
 - 1 LED 15 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
 - Strobe effect
 - The device is cooled by passive convection cooling
 - Control via master/slave function; stand-alone; IR remote control; sound to light via microphone; QuickDMX
 - Fixtures available for LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
 - Flicker-free
 - With a beam angle of 8°
 - For application areas such as: Wedding/gala/events; small rental
 - Silent operation
- device**
- Cordless, flexible and versatile
 - Battery operation up to 18h depending on program used

Logistic

EAN / GTIN: 4026397601367

Weight: 1,90 kg

Length: 0.27 m

Width: 0.20 m

Height: 0.11 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz 12.6V DC 2500 mA
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Battery/battery pack Mains input via coaxial power connector (M) mounting version power supply cord with Euro plug (provided)
Lamp type:	LED lamp
LED type:	1 x 15 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
DMX channels:	3; 4; 6; 8; 10
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Master/slave function; stand-alone; IR remote control; sound to light via microphone; QuickDMX
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
Beam angle:	8°
Beam angle (1/2 peak):	8°
Housing color:	Silver
Dimensions:	Width: 16.8 cm Depth: 13.8 cm Height: 6.2 cm
Weight:	1.67 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Battery pack type:	1 x lithium ion 11.1 V, 2600 mAh, 28.86 Wh
Battery pack:	Battery operation up to 18h depending on program used Recharging time 4h
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

- 1 x remote control
- 1 x device
- 1 x user manual
- 1 x external mains adapter