

## EUROLITE AKKU IP Flat Light 3 bl

Flat IP65 spotlight with 3 x 8 W RGBW LED, QuickDMX transceiver and bracket

Art. No.: 4170020

GTIN: 4026397686395



**List price: 296.31 €**

incl. 19% VAT.

### Features:

- Integrated QuickDMX transceiver for wireless DMX control
  - Cordless and versatile
  - Integrated automatic charging of the battery with indicator
  - Stepless color blend, color change, preset colors, dimmer and strobe effect
  - Dimmer speed (step response) adjustable
  - Battery operation up to 16h depending on program used
  - 3 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
  - Can be operated in 3; 4; 6; 8; 10 CH mode
  - The device is cooled by passive convection cooling
  - Controlling by Master/slave function; IR remote control; QuickDMX; stand-alone; Sound to light via Microphone
  - Preprogrammed in Light´J; Light Captain
  - Flicker-free
  - With a beam angle of 15°
  - With Mounting bracket
  - LCD display for easy controlling
  - Suitable for outdoor use IP65
  - For application areas such as: Small lender; Lender; Wedding/gala/events
- Package contents**
- 1 x device, 1 x external mains adapter, 1 x power cord, 1 x remote control, 1 x battery, 1 x declaration of conformity, 1 x user manual

### Logistic

EAN / GTIN: 4026397686395

Weight: 1,90 kg

Length: 0.27 m

Width: 0.20 m

Height: 0.11 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz 12,6 V DC 2,5 A
IP classification:	IP65
Protection class:	Class III
Power connection:	Mains input via Coaxial power connector (M) power supply cord with Euro plug (provided) Battery/battery pack
Battery pack type:	2 x lithium ion 11,1 V, 2600 mAh, 28,86 Wh
Battery pack:	Battery operation up to 16h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED:	3 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 10
Cooling:	Passive convection cooling
Control:	Master/slave function; IR remote control; QuickDMX; stand-alone; Sound to light via Microphone; Light J; Light Captain
Beam angle:	15°
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	33°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Carrier frequency:	2,4 GHz
Dimensions:	Width: 17,2 cm Depth: 13,8 cm Height: 6,2 cm
Weight:	1,61 kg
Remote control	
Battery:	1 x Button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting