

## EUROLITE AKKU Dot 1 RGB/WW QuickDMX bk

Art. No.: 4170060

Battery-powered pinspot with magnetic base, 15 W 4in1 LED, QuickDMX, frost filter and IR remote control GTIN: 4026397680928



### Features:

- Integrated QuickDMX transceiver for wireless DMX control
- Magnetic base affixes to metal surfaces
- Additional frost filter provides a wide, soft and homogeneous light
- Cordless, flexible and versatile
- Battery operation up to 18h depending on program used
- Integrated automatic charging of the battery and status indicator
- 1 LED 15 W SMD 9080 4in1 QCL RGB/WW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; white balance adjustable; Dimmer speed (step response) adjustable
- Strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via IR remote control; stand-alone; sound to light via microphone; QuickDMX; master/slave function; DMX
- Fixtures available for LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; Light Captain; EASY SHOW 2; EASY SHOW 3
- Flicker-free
- With a beam angle of 9°
- With mounting bracket
- Monochrome OLED display
- With a KENSINGTON LOCK theft protection
- For application areas such as: Small rental; wedding/gala/events; mobile djs / entertainer
- Application possibility: Standing; suspended
- Silent operation

### Logistic

EAN / GTIN: 4026397680928  
Weight: 1,70 kg  
Length: 0.25 m  
Width: 0.22 m  
Height: 0.15 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz 12.6V DC 200 mA
Power consumption:	25 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Battery/battery pack built-in Mains input via coaxial power connector (M) mounting version
Battery pack type:	1 x lithium ion 11.1 V, 5200 mAh, 57.72 Wh
Battery pack:	Battery operation up to 18h depending on program used Recharging time 3.5h
Lamp type:	LED lamp
LED type:	1 x 15 W SMD 9080 4in1 QCL RGB/WW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 11
Cooling:	Passive convection cooling
Control:	IR remote control; stand-alone; sound to light via microphone; QuickDMX; master/slave function; DMX
Fixtures available for:	LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
Beam angle (1/2 peak):	9°
Beam angle (1/10 peak):	18°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	Monochrome OLED display
Theft protection:	KENSINGTON LOCK
Dimensions:	Width: 11.1 cm Depth: 7.8 cm Height: 17.5 cm
Weight:	1.35 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

## Scope of delivery:

---

- 1 x spotlight
- 1 x user manual
- 1 x external mains adapter
- 1 x declaration of conformity
- 1 x frost filter
- 1 x remote control
- 1 x battery
- 1 x power cord