

EUROLITE AKKU IP BAR-6 Entry QCL QuickDMX

Weather-proof (IP65) battery-powered light bar with RGBW LEDs, QuickDMX and IR remote control

Art. No.: 41700105

GTIN: 4026397738643



Features:

- Cordless, flexible and versatile
- Battery operation up to 9h depending on program used
- Integrated automatic charging of the battery and status indicator
- 6 LEDs 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
- Dimmer; color blend; color fade
- Wash effect; strobe effect
- 9 integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; QuickDMX; IR remote control; wireless Master/slave function
- Flicker-free
- DMX fail mode (blackout; hold; full on; static; auto)
- With a beam angle of 17°
- Variable color temperature 2700 K - 8000 K
- With mounting bracket; with bracket for floor use
- LCD display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Architecture; clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels
- Silent operation
- Application possibility: Standing; suspended

Logistic

EAN / GTIN: 4026397738643

Weight: 5,80 kg

Length: 0.57 m

Width: 0.20 m

Height: 0.21 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug Battery/battery pack built-in
Cable construction:	3 x 1.0 mm ² H05RN-F
Power output:	IP T-Con (F) mounting version
Battery pack type:	1 x lithium ion 22.2 V, 2200 mAh, 48.84 Wh
Battery pack:	Battery operation up to 9h depending on program used Recharging time 3h
Lamp type:	LED lamp
LED type:	6 x 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0.5 - 23 Hz
DMX channels:	3; 4; 5; 6; 10
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; QuickDMX; IR remote control; wireless Master/slave function
Projection:	Flicker-free
PWM frequency:	5000 Hz
Carrier frequency:	2.4 GHz
Modulation:	GFSK
DMX fail mode:	Blackout; hold; full on; static; auto
Beam angle:	17°
Beam angle (1/2 peak):	17°
Beam angle (1/10 peak):	34°
Color temperature:	2700K - 8000K adjustable
Housing color:	Black
Attachment system:	Mounting bracket Bracket for floor use
Display type:	LCD display
Diameter mounting holes:	Ø11mm
Material:	Aluminum casting
Dimensions:	Length: 51.0 cm Depth: 16.0 cm Height: 14.5 cm
Weight:	5.30 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

- 1 x spotlight
- 1 x power cord
- 1 x user manual
- 1 x remote control
- 1 x battery