

EUROLITE AKKU Bar-6 QCL

Battery-powered LED bar with 4in1 LEDs and IR remote control

Art. No.: 41700122

GTIN: 4026397673364



Features:

- Additional frost filter provides a wide, soft and homogeneous light
- Cordless, flexible and versatile
- Integrated automatic charging of the battery and status indicator
- 6 LEDs 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix) LEDs controlled separately
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- Integrated show programs
- Direct color selection for 35 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; master/slave function; sound to light via microphone; IR remote control; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional)
- Fixtures available for LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light´J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 8°
- With double bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental
- Silent operation
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397673364

Weight: 4,27 kg

Length: 0.56 m

Width: 0.13 m

Height: 0.26 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Battery/battery pack Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Battery pack type:	1 x lithium ion 11.1 V, 10400 mAh, 115.44 Wh
Lamp type:	LED lamp
LED type:	6 x 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
DMX channels:	4; 6; 8; 11; 12; 13; 17; 24; 29
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; master/slave function; sound to light via microphone; IR remote control; W- DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional)
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	8°
Beam angle (1/2 peak):	8°
Beam angle (1/10 peak):	17°
Housing color:	Black
Attachment system:	Double bracket
Dimensions:	Length: 50.2 cm Depth: 6 cm Height: 20.1 cm
Weight:	3.80 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x bar
1 x user manual
1 x power cord
1 x frost filter
1 x remote control
1 x battery