

## EUROLITE AKKU MBT-3 Spot MK2

Light fan for special uplight and beam effects with rechargeable battery

Art. No.: 41700150

GTIN: 4026397722642



**List price: 355.81 €**

incl. 19% VAT.

### Features:

- Strobe effect; fan effect; uplight effect
- Cordless, flexible and versatile
- Silent operation
- 3 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix) LEDs controlled separately
- 9 integrated show programs
- Direct color selection for 15 preset colors
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) with adjustable response
- Battery operation up to 16h depending on program used
- Control via stand-alone; Master/slave function; Sound to light via Microphone; IR remote control; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Integrated automatic charging of the battery and status indicator
- Flicker-free
- Space-saving construction
- With a beam angle of 13°
- 4 digit 7-segment LED display
- The device is cooled by passive convection cooling
- Mains input and output for power linking up to 8 units
- Application possibility: Standing; suspended
- Preprogrammed in Light J; Light Captain; EASY SHOW 1; EASY SHOW 3; EASY SHOW 2
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental

### Package contents

- 1 x device, 1 x power cord, 1 x user manual, 1 x remote control, 1 x battery

### Logistic

EAN / GTIN: 4026397722642

Weight: 4,40 kg

Length: 0.34 m

Width: 0.25 m

Height: 0.16 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Cable length:	1,5 m
Power output:	IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 1,6 A Fuse replaceable
Battery pack type:	1 x lithium ion 14,8 V, 6600 mAh, 97,68 Wh
Battery pack:	Battery operation up to 16h depending on program used Recharging time 4h
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Lamp type:	LED lamp
LED:	3 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
Inclination angle:	180 °
Flash rate:	0 - 25 Hz
DMX channels:	3; 4; 8; 12; 16
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; Master/slave function; Sound to light via Microphone; IR remote control; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light'J; Light Captain; EASY SHOW 1; EASY SHOW 3; EASY SHOW 2
Projection:	Flicker-free
Setup:	Space-saving construction
Beam angle:	13°
Beam angle (1/2 peak):	13°
Housing color:	Black
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 30,5 cm Width: 9,5 cm Height: 22 cm
Weight:	4,15 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting