

EUROLITE AKKU MBT-3 Spot MK2

Light fan for special uplight and beam effects with rechargeable battery

Art. No.: 41700150 GTIN: 4026397722642









List price: 355.81 €

incl. 19% VAT.

Features:

- Strobe effect; fan effect; uplight effect
- Cordless, flexible and versatile
- Silent operation
- 3 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
 LEDs controlled separately
- 9 integrated show programs
- Direct color selection for 15 preset colors
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic;
 Dimmer speed (step response) with adjustable response
- Battery operation up to 16h depending on program used
- Control via stand-alone; master/slave function; sound to light via microphone; IR remote control;
 DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional);
 CRMX by LumenRadio via USB (optional)
- Integrated automatic charging of the battery and status indicator
- Flicker-free
- Space-saving construction
- With a beam angle of 13°
- 4 digit 7-segment LED display
- The device is cooled by passive convection cooling
- Mains input and output for power linking up to 8 units
- Application possibility: Standing; suspended
- Preprogrammed in Light'J; Light Captain; EASY SHOW 1; EASY SHOW 3; EASY SHOW 2; Colorchief
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental

Package contents

Logistic

EAN / GTIN: 4026397722642

Weight: 4,40 kg Length: 0.34 m Width: 0.25 m Heigth: 0.16 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz	
IP classification:	IP20	
Protection class:	Protection class I	
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)	
Cable length:	h: 1,5 m	
ower output: IEC connector (F) mounting version		
Fuse:	5 x 20 mm, T 1,6 A fuse replaceable	
Battery pack type:	1 x lithium ion 14,8 V, 6600 mAh, 97,68 Wh	
Battery pack:	Battery operation up to 16h depending on program used	
	Recharging time 4h	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in	
Lamp type: LED lamp		
LED type:	3 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)	
Inclination angle:	180 °	
Flash rate:	0 - 25 Hz	
DMX channels:	3; 4; 8; 12; 16	
DMX input:	3-pin XLR (M) mounting version	
DMX output:	3-pin XLR (F) mounting version	
Cooling:	Passive convection cooling	
Control:	ntrol: Stand-alone; master/slave function; sound to light via microphone; IR remote control; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)	
reprogrammed in: Light'J; Light Captain; EASY SHOW 1; EASY SHOW 3; EASY SHOW 2; Colorchief		
Projection:	Flicker-free	
Setup:	Space-saving construction	
Beam angle:	13°	
Beam angle (1/2 peak):	e (1/2 peak): 13°	
Housing color:	Black	
Display type:	4 digit 7-segment LED display	
Dimensions:	Length: 30,5 cm	
	Width: 9,5 cm Height: 22 cm	
Weight:	4,15 kg	
Noise classification:	Class 0 (no noise at all)	
Legal specifications		
Special product:	Not designed for household room illumination	
Special product. Not designed for flousefiold footh illumination		

Intended use:	Show effect lighting