

EUROLITE AKKU TL-3 TCL Trusslight QuickDMX

Spot for lighting within trussing, 3 x 3 W 3in1 LED, QuickDMX transceiver

Art. No.: 41700501

GTIN: 4026397602234



List price: 202.18 €

incl. 19% VAT.

Description:

The AKKU TL-3 TCL Trusslight QuickDMX is a spotlight equipped with 3 bright 3-watt RGB LEDs (3in1) for lighting within trussing. It is wireless and battery-run (battery life 16 hours) and its small size makes it a great fit for many 3- and 4-point trussing systems. Furthermore, this device is equipped with a built-in QuickDMX transceiver for wireless transmission of DMX512 signals.

You can choose from a variety of different functions such as static colors, continuous RGB color mixture, internal programs, dimmer effects as well as strobe effects with adjustable speed.

The device can either be controlled via DMX or the supplied wireless remote control (Eurolite IR-13).

All of these features make the AKKU TL-3 TCL the perfect choice for booth construction, stages and any kind of truss.

Logistic

EAN / GTIN: 4026397602234

Weight: 1,44 kg

Length: 0.16 m

Width: 0.16 m

Height: 0.19 m

Features:

- Compact and bright
- Ideal for ALUTRUSS DECOLOCK DQ3 3-point system
- Integrated QuickDMX transceiver for wireless DMX control
- Threaded inserts for suspended installation
- Battery operation up to 16h depending on program used
- 3 powerful LEDs 3 W high-power 3in1 TCL RGB (homogenous color mix)
- Dimmer electronic; color blend stepless; color change adjustable; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; QuickDMX; IR remote control; sound to light via microphone

- Flicker-free
- With a beam angle of 11°
- LCD display
- For application areas such as: Wedding/gala/events; mobile use; stage; mobile djs / entertainer
- Mains input and output for power linking up to 8 units
- Cordless, flexible and versatile
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- 3 rubber feet
- Silent operation
- Application possibility: Standing; suspended

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 1 x declaration of conformity

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	25 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Battery/battery pack Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Cable length:	Approx. 1,2 m
Power output:	1 x IEC connector (F) mounting version
Fuse:	5 x 20 mm, F 5 A
Battery pack type:	1 x lithium ion 11,1 V, 4400 mAh, 48,84 Wh
Battery pack:	Battery operation up to 16h depending on program used Recharging time 3h
Lamp type:	LED lamp
LED type:	3 x 3 W high-power 3in1 TCL RGB (homogenous color mix)
Flash rate:	0 - 23 Hz
DMX channels:	3; 5; 8
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; QuickDMX; IR remote control; sound to light via microphone
Preprogrammed in:	Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	11°
Beam angle (1/2 peak):	11°

Beam angle (1/10 peak):	24°
Housing color:	Black
Attachment system:	M10 thread
Display type:	LCD display
Transport aid:	3 x rubber feet
Dimensions:	Width: 12,1 cm Depth: 10,8 cm Height: 14,5 cm
Weight:	1,27 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting