

## EUROLITE AKKU UP-4 QCL Spot WDMX

Uplight with 4 x 8 W 4in1 LED & wireless DMX receiver (Wireless Solution)

Art. No.: 41700555

GTIN: 4026397531893



**The article is no longer in our assortment.**

### Features:

- Compact and bright
  - Equipped with 4 x 8 W QCL LED in red, green, blue and white
  - With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
  - Operation via mains connection or built-in rechargeable lithium-ion battery with up to 8.5 hours operating time
  - Integrated automatic charging of the battery with indicator
  - Controllable via EUROLITE IR-7 remote control; included in the delivery
  - With integrated folding foot for angled placement by floor installation
  - DMX-controlled operation or stand-alone operation with Master/Slave function
  - 4, 6 or 10 DMX channels selectable
  - Functions: static colors, stepless RGBW color mixture, internal programs, dimmer, strobe effect with variable speed, sound-control
  - Dimmer speed (step response) adjustable
  - Adjustable microphone sensitivity
  - Addressing via control panel with 4-digit LED display
  - Switch-mode power supply for operation between 100 and 240 volts
  - Ready for connection via included power cable with safety power plug
  - Feed-through output allows to power up to 8 devices
  - 4 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
  - The device is cooled by passive convection cooling
  - Control via DMX; stand-alone; W-DMX by wireless solution; Sound to light via Microphone
  - Pre-programmed in Light 'J'; LED PC-Control 512
  - Flicker-free
  - With a beam angle of 13°
- device**
- Cordless, flexible and versatile

### Logistic

EAN / GTIN: 4026397531893

Weight: 3,20 kg

Length: 0.23 m

Width: 0.20 m

Height: 0.27 m

- Battery operation up to 8,5h
- Package contents**
- 1 x device, 1 x remote control

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	45 W
IP classification:	IP20
Power connection:	Battery/battery pack Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED:	4 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
DMX channels:	4; 6; 10
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; W-DMX by wireless solution; Sound to light via Microphone
Preprogrammed in:	Light´J; LED PC-Control 512
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	13°
Beam angle (1/2 peak):	13°
Housing color:	Black
Dimensions:	Width: 13,8 cm Depth: 14,5 cm Height: 19,1 cm
Weight:	2,90 kg
Device	
Battery pack type:	1 x lithium ion 14,8 V, 6600 mAh, 97,68 Wh
Battery pack:	Battery operation up to 8,5h Recharging time 5h
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting