

EUROLITE AKKU UP-4 HCL Spot WDMX wh

LED Uplight with 4 x 12 W 6in1 LED & wireless DMX receiver (Wireless Solution)

Art. No.: 41700561

GTIN: 4026397550863



The article is no longer in our assortment.

Features:

- Compact and bright
- Equipped with 4 x 12 W HCL LED in red, green, blue, amber, white and UV
- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- Operation via mains connection or built-in rechargeable lithium-ion battery with up to 8.5 hours operating time
- Integrated automatic charging of the battery with indicator
- Controllable via EUROLITE IR-7 remote control; included in the delivery
- With integrated folding foot for angled placement by floor installation
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 6, 8 or 12 DMX channels selectable
- Functions: static colors, stepless RGBAW+UV color mixture, internal programs, dimmer, strobe effect with variable speed, sound-control
- Dimmer speed (step response) adjustable
- Adjustable microphone sensitivity
- Addressing via control panel with 4-digit LED display
- Switch-mode power supply for operation between 100 and 240 volts
- Ready for connection via included power cable with safety power plug
- Feed-through output allows to power up to 8 devices
- DMX control via any standard DMX controller
- Available in 2 housing colors: black and white
- 4 powerful LEDs 12 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; W-DMX by wireless solution; sound to light via microphone
- Preprogrammed in Light'J; LED PC-Control 512
- Flicker-free
- With a beam angle of 22°

Logistic

EAN / GTIN: 4026397550863

Weight: 3,20 kg

Length: 0.23 m

Width: 0.20 m

Height: 0.27 m

device

- Cordless, flexible and versatile
- Battery operation up to 8,5h depending on program used

Package contents

- 1 x device, 1 x remote control

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	37 W
IP classification:	IP20
Power connection:	Battery/battery pack Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	4 x 12 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
DMX channels:	6; 8; 12
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; W-DMX by wireless solution; sound to light via microphone
Preprogrammed in:	Light'J; LED PC-Control 512
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	22°
Beam angle (1/2 peak):	22°
Housing color:	White
Dimensions:	Width: 13,8 cm Depth: 14,5 cm Height: 19,1 cm
Weight:	2,90 kg
Device	
Battery pack type:	1 x lithium ion 14,8 V, 6600 mAh, 97,68 Wh
Battery pack:	Battery operation up to 8,5h depending on program used Recharging time 4,5h
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting