eurolite®

EUROLITE AKKU UP-4 Entry QCL Spot

Battery-powered uplight with 4 x 8 W 4in1 LED and IR remote control

Art. No.: 41700575

GTIN: 4026397691603









List price: 213.01 €

incl. 19% VAT.

Features:

- Sturdy housing with handle and folding foot for angled placement
- Battery operation up to 14h depending on program used
- 4 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Energysaving mode
- Strobe effect
- Integrated show programs
- Direct color selection for 17 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 17°
- 4 digit 7-segment LED display
- Preprogrammed in Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light'J; Colorchief
- Mains input and output for power linking up to 8 units
- Application possibility: Standing
- Cordless, flexible and versatile
- Integrated automatic charging of the battery and status indicator
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental
- Silent operation
- Package contents
- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

Logistic

EAN / GTIN: 4026397691603 Weight: 2,55 kg Length: 0.20 m Width: 0.20 m Heigth: 0.23 m

Technical specifications:

| · · · | |
|-------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output: | IEC connector (F) mounting version |
| Fuse: | T 1 A fuse replaceable |
| Battery pack type: | 1 x lithium ion 11,1 V, 4400 mAh, 48,84 Wh |
| Battery pack: | Battery operation up to 14h depending on program used |
| | Recharging time 4h |
| Lamp type: | LED lamp |
| LED type: | 4 x 8 W high-power 4in1 QCL RGBW (homogenous color mix) |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 3; 4-1; 4; 6; 8 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W- DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Preprogrammed in: | Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light'J; Colorchief |
| Projection: | Flicker-free |
| Beam angle: | 17° |
| Beam angle (1/2 peak): | 17° |
| Beam angle (1/10 peak): | 34° |
| Housing color: | Black |
| Attachment system: | M10 thread |
| Display type: | 4 digit 7-segment LED display |
| Dimensions: | Width: 14,4 cm Depth: 14,4 cm Height: 19,1 cm |
| Weight: | 2,35 kg |
| Noise classification: | Class 0 (no noise at all) |
| Remote control | |
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| | |