

## EUROLITE AKKU IP UP-4 Plus HCL Spot CRMX MK2

IP65 uplight with replaceable battery, RGBWA+UV LEDs, CRMX and IR remote control

**Art. No.: 41700583**

GTIN: 4026397745603

**The article is no longer in our assortment.**

### Features:

- Integrated wireless receiver for CRMX operation
- Sturdy metal housing with handle and folding foot for angled placement
- Battery pack tool-free replacement
- Battery operation up to 7,4h 100%; battery operation up to 13,5h 50%
- Integrated automatic charging of the battery and status indicator
- 4 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Dimmer stepless; Dimmer speed (step response) with adjustable response; color fade adjustable speed; color change adjustable speed; white balance user-definable; color blend adjustable; color macros; program selection manual; Energy-saving mode adjustable
- 51 integrated show programs
- Direct color selection for 63 preset colors
- The device is cooled by passive convection cooling
- Cordless, flexible and versatile
- Control via IR remote control; CRMX by LumenRadio; stand-alone
- DMX fail mode (blackout; hold; full on; auto)
- With a beam angle of 10°
- With bracket for floor use
- Monochrome OLED display
- Display of the remaining battery life for the current setting
- Suitable for outdoor use IP65
- With a KENSINGTON LOCK theft protection
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; video and photography
- Silent operation
- Application possibility: Standing
- 3 buttons on the remote control for saving your own settings

### Logistic

EAN / GTIN: 4026397745603

- Rubber feet
- Flicker-free
- Frost filter

#### Package contents

- 1 x spotlight, 1 x power cord, 1 x charger, 1 x remote control, 1 x frost filter, 2 x knurled screw, 1 x plate, 1 x user manual, 1 x declaration of conformity, 1 x battery pack

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz 12,6V DC 3000 mA
Pin configuration:	Inside + / outside -
IP classification:	IP65
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with Euro plug (provided)
Battery pack type:	1 x lithium ion 11,1 V, 13000 mAh, 144,3 Wh
Battery pack:	Battery operation up to 7,4h 100% Recharging time 7,7h Battery operation up to 13,5h 50% Recharging time 7,7h
Lamp type:	LED lamp
LED type:	4 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
Flash rate:	1 - 27 Hz
Equipment:	Frost filter
DMX channels:	6; 8; 12
Cooling:	Passive convection cooling
Control:	IR remote control; CRMX by LumenRadio; stand- alone
Projection:	Flicker-free
PWM frequency:	3000 Hz
Carrier frequency:	2,4 GHz
Modulation:	GFSK
DMX fail mode:	Blackout; hold; full on; auto
Beam angle:	10°
Beam angle (1/2 peak):	10° Frost filter 20°
Beam angle (1/10 peak):	20° Frost filter 45°
Housing color:	Black matte
Attachment system:	Bracket for floor use
Display type:	Monochrome OLED display
Display:	Battery runtime calculation
Status LED:	Charge status indicator
Transport aid:	Rubber feet
Material:	Metal, painted
Theft protection:	KENSINGTON LOCK

Dimensions:	Length: 17,1 cm Width: 13,8 cm Height: 20 cm
Weight:	4,5 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell CR2032
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting