

EUROLITE AKKU IP UP-4 Entry QCL Spot QuickDMX

IP65 battery-powered uplight with RGBW LEDs, QuickDMX and IR remote control

Art. No.: 41700585

GTIN: 4026397691610



List price: 308.21 €

incl. 19% VAT.

Features:

- Integrated QuickDMX transceiver for wireless DMX control
- Diffuser covers with 40° and elliptical 15° x 60° beam angle optional
- Direct color selection for 19 preset colors
- Stepless color blend, color change, color fade, dimmer and strobe effect
- Sturdy metal housing with handle and folding foot for angled placement
- Battery operation up to 12h depending on program used
- 4 powerful LEDs 8 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- Integrated Showprograms
- Can be operated in 3; 4; 5; 6; 9 CH mode
- The device is cooled by passive convection
- Controlling by stand-alone; IR remote control; DMX; Master/slave function; QuickDMX built-in
- Preprogrammed in Light Captain
- Flicker-free projection
- With a beam angle of 16°
- OLED display for easy controlling
- With 4 rubber feet
- Suitable for outdoor use

Logistic

EAN / GTIN: 4026397691610

Weight: 4,90 kg

Length: 0.26 m

Width: 0.21 m

Height: 0.27 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

IP classification: IP65

Protection class: Class I

Power connection:	Battery/battery pack built-in Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Battery pack type:	1 x lithium ion 11,1 V, 4400 mAh, 48,84 Wh
Battery pack:	Battery operation up to 12h depending on program used Recharging time 3h
Lamp type:	LED lamp
LED:	4 x 8 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
DMX channels:	3; 4; 5; 6; 9
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection
Control:	Stand-alone; IR remote control; DMX; Master/slave function; QuickDMX built-in; Light Captain
Beam angle:	16°
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	32
Housing color:	Black
Display type:	OLED display
Carrier frequency:	2,4 GHz
Transport aid:	4 x rubber feet
Dimensions:	Width: 19,00 cm Depth: 15,50 cm Height: 23,25 cm
Weight:	4,50 kg
Remote control	
Battery:	Button cell 3.0 V CR2025 lithium manganese (provided)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting