

## EUROLITE AKKU LP-20 Gobo Projector QuickDMX

LED gobo projector with 20 W LED, QuickDMX, strobe, dimmer and gobo rotation

Art. No.: 41700650

GTIN: 4026397655537



**The article is no longer in our assortment.**

### Features:

- Ideal as a logo projector, both for mobile and stationary use
- Integrated QuickDMX transceiver for wireless DMX control
- Suitable for metal gobos with an outside/image diameter of 27/18 mm
- Delivery includes a gobo, motive "bubbles"
- Clear projection
- Cordless, flexible and versatile
- Battery operation up to 9h depending on program used
- Integrated automatic charging of the battery and status indicator
- 1 powerful LED 20 W COB (chip-on-board) cold white (CW)
- Gobo wheel with rotating gobos; focus manual
- Dimmer electronic; color macros adjustable; Rotation speed adjustable; Rotation direction adjustable
- Gobo effect; strobe effect
- Gobos changeable
- The device is cooled by passive convection cooling
- Control via QuickDMX; IR remote control
- Preprogrammed in Light´J; Light Captain
- Flicker-free
- With a beam angle of 11° - 16°
- With double bracket
- With a KENSINGTON LOCK theft protection
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation
- Application possibility: Standing; suspended; on stand

### Package contents

### Logistic

EAN / GTIN: 4026397655537

Weight: 5,12 kg

Length: 0.31 m

Width: 0.22 m

Height: 0.31 m

- 1 x device, 1 x user manual, 1 x power cord, 1 x gobos, 1 x remote control

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) Battery/battery pack
Cable length:	Approx. 1,2 m
Battery pack type:	1 x lithium ion 25,9 V, 7800 mAh, 202,02 Wh
Battery pack:	Battery operation up to 9h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED type:	1 x 20 W COB (chip-on-board) cold white (CW)
Equipment:	Gobo wheel with rotating gobos; focus manual
Gobos:	Outside diameter 27mm Image diameter 18mm Gobos changeable
DMX channels:	2; 3; 4
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	QuickDMX; IR remote control
Preprogrammed in:	Light´J; Light Captain
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	11° - 16°
Beam angle (1/2 peak):	11 - 16°
Beam angle (1/10 peak):	11 - 16°
Housing color:	Black
Attachment system:	Double bracket
Theft protection:	KENSINGTON LOCK
Dimensions:	Width: 19,3 cm Depth: 25,6 cm Height: 28,7 cm
Weight:	4,70 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	Button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting