

EUROLITE AKKU IP PAR 7 QCL WDMX

IP65 battery-powered spotlight with RGBW LEDs, WDMX, frost filters and IR remote control

Art. No.: 41700790

GTIN: 4026397676730



List price: 593.81 €

incl. 19% VAT.

Features:

- With integrated wireless transceiver for WDMX operation (Wireless Solution - made in Sweden)
- 7 high-power 8 W RGBW LEDs (4in1)
- Two additional frost filters provide a soft, homogeneous light
- 8° beam angle; 2 frost filters (15° and 19°) included in delivery
- Operation via built-in rechargeable lithium-ion battery with up to 9 hours operating time
- Integrated automatic charging of the battery with indicator
- Suitable for external use (IP65)
- Auto, music, master/slave and DMX/WDMX mode
- 36 professionally designed integrated show programs, sorted by colors and themes
- Direct color selection for 15 preset colors
- Stepless RGBW color mixture, color change, color fade, dimmer, strobe effect with variable speed, white balance
- Dimmer speed (step response) adjustable
- Addressing and setting via control panel with touch buttons and OLED display
- Convenient wireless control via included IR remote control EUROLITE IR-35
- Swivel mounting brackets
- Additional bracket for floor use
- IP T-Con terminals for power linking up to 8 units
- Switch-mode power supply for operation between 100 and 240 volts
- LED: 7 x high-power 8 W 4in1 QCL RGBW (homogenous color mix)
- Can be operated in 3; 4; 6; 8; 11 CH mode
- The device is cooled by passive convection
- Controlling by DMX; W-DMX by wireless solution built-in; Stand-alone; IR remote control; Master/slave function; Sound to light via Microphone
- Is in EASY SHOW; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J Software already preprogrammed

Logistic

EAN / GTIN: 4026397676730
 Weight: 5,80 kg
 Length: 0.23 m
 Width: 0.24 m
 Height: 0.34 m

- Flicker-free projection
- Suitable for outdoor use
- With a KENSINGTON LOCK theft protection

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	70 W
IP classification:	IP65
Protection class:	Class I
Power connection:	Battery/battery pack Mains input IP T-Con (M) mounting version Power supply cord with safety plug (provided)
Cable length:	Approx. 1,2 m
Power output:	1 x IP T-Con (F) mounting version
Battery pack type:	1 x lithium ion 25,9 V, 7800 mAh, 202,02 Wh
Battery pack:	Battery operation up to 9h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED:	7 x high-power 8 W 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection
Control:	DMX; W-DMX by wireless solution built-in; Stand-alone; IR remote control; Master/slave function; Sound to light via Microphone; EASY SHOW; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J Software
Beam angle:	8°
Beam angle (1/2 peak):	8° 15° 19°
Beam angle (1/10 peak):	15°
Housing color:	Black
Carrier frequency:	2,4 GHz
Theft protection:	KENSINGTON LOCK
Dimensions:	Width: 23,4 cm Depth: 28,0 cm Height: 17,0 cm
Weight:	5,25 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x Button cell 3.0 V CR2032 lithium manganese built-in

Legal specifications

Special product: Not designed for household room illumination

intended use: show effect lighting
