

## EUROLITE AKKU KLS-180 Compact Light Set

Complete DMX LED lighting system with rechargeable battery pack

Art. No.: 41701000

GTIN: 4026397676440



**List price: 439.11 €**

incl. 19% VAT.

### Features:

- Crossbar with integrated DMX control unit and stand sleeve
  - Movable and tiltable spotlights
  - Battery operation up to 20h depending on program used
  - Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Energy-saving mode
  - Strobe effect
  - Integrated show programs
  - Direct color selection for 20 preset colors
  - The device is cooled by passive convection cooling
  - Control via stand-alone; Sound to light via Microphone; DMX; IR remote control; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
  - Flicker-free
  - With a beam angle of 9°
  - 4 digit 7-segment LED display
  - For application areas such as: Band/rehearsal room; mobile djs / entertainer; Stage; small rental; mobile use
  - Silent operation
  - Preprogrammed in EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3; Light J
  - Mains input and output for power linking up to 8 units
  - Application possibility: On stand; suspended
  - Cordless, flexible and versatile
  - Integrated automatic charging of the battery and status indicator
- spotlight**
- 4 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix) <BR> spots controlled separately

### Logistic

EAN / GTIN: 4026397676440

Weight: 7,20 kg

Length: 0.68 m

Width: 0.21 m

Height: 0.33 m

**bar**

- 4 powerful LEDs 1 W high-power cold white (CW)<BR> LEDs controlled separately

**Package contents**

- 1 x light effect, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 1 x bag

**Technical specifications:**

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP20
Power connection:	Battery/battery pack Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Fuse:	T 1 A Fuse replaceable
Battery pack type:	1 x lithium ion 22,2 V, 4400 mAh, 97,68 Wh
Battery pack:	Battery operation up to 20h depending on program used Recharging time 5h
Lamp type:	LED lamp
DMX channels:	3; 4; 8; 21
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; Sound to light via Microphone; DMX; IR remote control; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3; Light J
Projection:	Flicker-free
Beam angle:	9°
Beam angle (1/2 peak):	9°
Housing color:	Black
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 61 cm Depth: 14,5 cm Height: 27,4 cm
Weight:	5,90 kg
Noise classification:	Class 0 (no noise at all)
<b>Spotlight</b>	
LED:	4 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
<b>Bar</b>	
LED:	4 x 1 W high-power cold white (CW)
Flash rate:	0 - 20 Hz
<b>Remote control</b>	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in

Legal specifications

---

Special product: Not designed for household room illumination

---

Intended use: Show effect lighting

---