

EUROLITE AKKU KLS-180 Compact Light Set

Complete DMX LED lighting system with rechargeable battery pack

Art. No.: 41701000

GTIN: 4026397676440



Features:

- Crossbar with integrated DMX control unit and stand sleeve
- Movable and tiltable spotlights
- Cordless, flexible and versatile
- Battery operation up to 20h depending on program used
- Integrated automatic charging of the battery and status indicator
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Energy-saving mode
- Strobe effect
- Integrated show programs
- Direct color selection for 20 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; sound to light via microphone; DMX; IR remote control; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief
- Flicker-free
- With a beam angle of 9°
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels
- Silent operation
- Application possibility: On stand; suspended

spotlight

Logistic

EAN / GTIN: 4026397676440

Weight: 7,20 kg

Length: 0.68 m

Width: 0.21 m

Height: 0.33 m

- 4 LEDs 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
 spots controlled separately

bar

- 4 LEDs 1 W SMD 8072 cold white (CW)
 LEDs controlled separately

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP20
Power connection:	Battery/battery pack Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Fuse:	T 1 A fuse replaceable
Battery pack type:	1 x lithium ion 22.2 V, 4400 mAh, 97.68 Wh
Battery pack:	Battery operation up to 20h depending on program used Recharging time 5h
Lamp type:	LED lamp
Flash rate:	0.5 - 20 Hz
DMX channels:	3; 4; 8; 21
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; sound to light via microphone; DMX; IR remote control; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief
Projection:	Flicker-free
PWM frequency:	3000 Hz
Beam angle:	9°
Beam angle (1/2 peak):	9°
Housing color:	Black
Display type:	4 digit 7-segment LED display
Material:	Metal; plastic
Dimensions:	Width: 61 cm Depth: 14.5 cm Height: 27.4 cm
Weight:	5.90 kg
Noise classification:	Class 0 (no noise at all)
LED type:	4 x 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
LED type:	4 x 1 W SMD 8072 cold white (CW)
Diameter mounting holes:	3 x Ø11mm; 2 x Ø3mm
Material:	Metal, 2 mm

Cable construction:	3 x 0.75 mm ² H05VV-F
Cable length:	Approx. 1.2 m
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

- 1 x light effect
- 1 x power cord
- 1 x remote control
- 1 x battery
- 1 x bag
- 1 x user manual