

EUROLITE PAR-56 Spot CDM150 sil

Long PAR-56 housing for CDM-T 150 discharge lamps


Art. No.: 42000910 GTIN: 4026397426946











incl. 19% VAT.

Features:

- Rugged metal housing
- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Protective shield is integrated in the tube
- Control via plug and play
- With a beam angle of 55°
- With mounting bracket
- For PAR 56
- For application areas such as: Theater; mobile use; Trade fair and shop fitting

Package contents

- 1 x spotlight, 1 x filter frame, 1 x user manual

Logistic

EAN / GTIN: 4026397426946

Weight: 4,50 kg Length: 0.27 m Width: 0.28 m Heigth: 0.46 m

Technical specifications:

| Power supply: | 230 V AC, 50 Hz |
|--------------------|--|
| Power consumption: | 210 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Fixed power supply cord with safety plug |
| Cable length: | Approx. 0,8 m |
| Base: | G-12 |
| Lamp type: | Discharge lamp |
| | |

| Color generation: | Via color filter frame (optional) |
|------------------------|--|
| Control: | Plug and play |
| Beam angle: | 55° |
| Beam angle (1/2 peak): | 55° |
| Housing color: | Silver |
| Attachment system: | Mounting bracket |
| Dimensions: | Length: 36 cm |
| | Width: 24 cm |
| | Height: 32 cm |
| Weight: | 4,00 kg |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |