

EUROLITE PAR-56 Spot CDM150 bk

Long PAR-56 housing for CDM-T 150 discharge lamps

Art. No.: 42000920

GTIN: 4026397491722



Features:

- Rugged metal housing
- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Protective shield is integrated in the tube
- Control via plug and play
- With a beam angle of 55°
- With mounting bracket
- For PAR 56
- For application areas such as: Trade fair and shop fitting; video and photography; advertisement/Shop window

Logistic

EAN / GTIN: 4026397491722

Weight: 4,50 kg

Length: 0.28 m

Width: 0.27 m

Height: 0.47 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	210 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable length:	Approx. 0.8 m
Base:	G-12
Lamp type:	Discharge lamp
Color generation:	Via color filter frame (optional)

Control:	Plug and play
Beam angle:	55°
Beam angle (1/2 peak):	55°
Housing color:	Black
Attachment system:	Mounting bracket
Dimensions:	Length: 36 cm Width: 24 cm Height: 32 cm
Weight:	4.05 kg
Dimensions:	Length: 22.8 cm Width: 22.8 cm Diameter: Ø 18 cm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x spotlight
1 x filter frame
1 x user manual